Evolving Alignment via Asymmetric Self-Play

Scalable Preference Fine-Tuning Beyond Static Human Prompts

Ziyu Ye^{*1,2}, Rishabh Agarwal¹, Tianqi Liu¹, Rishabh Joshi¹, Sarmishta Verlury¹, Quoc V. Le¹, Qijun Tan¹, Yuan Liu¹ ¹Google DeepMind, ²The University of Chicago

Current RLHF frameworks for aligning large language models (LLMs) typically assume a fixed prompt distribution, which is sub-optimal and limits the scalability of alignment and generalizability of models. To address this, we design a general Open-Ended RLHF framework that casts alignment as an asymmetric game between two players: (i) a creator that generates increasingly informative prompt distributions using reward signals, and (ii) a solver that learns to produce more preferred responses on prompts produced by the creator. This framework of Evolving Alignment <u>via Asymmetric Self-Play (eva)</u>, results in a simple and efficient approach that can utilize any existing RLHF algorithm for scalable alignment. eva outperforms state-of-the-art methods on widely-used benchmarks, without the need of any additional human crafted prompts. Specifically, eva improves the win rate of gemma2-9b-it on Arena-Hard from 51.6% to 60.1% with DPO, from 55.7% to 58.9% with SPPO, from 52.3% to 60.7% with SimPO, and from 54.8% to 60.3% with ORPO, surpassing its 27B version and matching claude-3-opus. This improvement is persistent even when new human crafted prompts are introduced. Finally, we show eva is effective and robust under various ablation settings.

Keywords: Self-Play, Reinforcement Learning from Human Feedback, Open-Ended Learning.



Figure 1 | **eva**. Open-Ended RLHF *via* Asymmetric Self-Play. The creator is the prompt generation policy π_X and the solver is the response generation policy $\pi_{Y|X}$.

What I cannot create, I do not understand.



Figure 2 | **Results**. Our method **eva** achieves concrete performance gain especially on *hard* alignment benchmarks, without relying on any additional human prompts. Here, we report results for DPO-**eva**; see more in § 4.1.

– Richard P. Feynman

1. Introduction

Long-lived artificial intelligence must deal with an ever-evolving, open-ended world, yet currently face constraints in both the *scale* and *quality* of available data, and the *growth rate* at which new, useful information is created. High-quality human data, crucial for scaling large language model based intelligence, is projected to run out in the next few years (Villalobos et al., 2024); the quality of such data is also expected to stagnate: as those large models become more capable, they need to identify and solve new and increasingly complex challenges, requiring training data beyond the capabilities of humans to create. This necessitates a new fundamental training mechanism, where models can continue to self-improve by generatively exploring and solving new problems. We thereby investigate the research question below:

Can language models identify and self-create new, learnable tasks to work on, to self-improve to generalize better for human preferences alignment?

Corresponding author(s): hazelye, yuanliu@google.com. **Work done in an internship at Gemini Team, Google.* © 2024 Google DeepMind. All rights reserved.



Figure 3 | **Pipeline**: We generalize classical RLHF with open-ended RLHF, optimized with a creator-solver game for self-improving language models. Our proposed **eva** strategically evolves prompt distributions with a creator policy, which synthesizes prompts with an easy-to-implement *estimate, sample then evolve* procedure; specifically, it estimates the informativeness for each prompt by how contrastive the self-generated responses are to the prompt, from the reward signals it receives. The creator evolves new prompts from highly informative prompts, which the solver uses for continual training. The solver and creator policy can share the same network or operate independently. See more on our minimax-regret objective that drives the above design in § 3.

Many preference optimization algorithms (Christiano et al., 2017; Guo et al., 2024; Liu et al., 2023a; Rafailov et al., 2023; Zhao et al., 2023) have been proposed to improve the alignment of language models, however, they all default to fixed prompt training distributions. Such fixed training paradigm inevitably leads to: (i) *generalization issues* (models may underperform or hack on instructions that are insufficiently represented in the fixed set) and (ii) *efficiency issues* (data annotation and model training are costly, however not all prompt provide the same utility; it is wasteful to invest in sub-optimal fixed set, while identifying informative prompts through human efforts is expensive and time-consuming) (Dubey et al., 2024; Team et al., 2023, 2024).

The objective thereby should not only be to optimize over a specific, static distribution of prompts, yet to develop an agent that can autonomously evolve the training data distribution for self-improvement, to align well across unseen, novel environments or tasks (instantiated by prompts).

Thus, we develop **eva** (Evolving Alignment <u>via</u> Asymmetric Self-Play), as illustrated in Figure 1. Central to our approach is a game with the minimax-regret objective, achieved through alternating optimization between creating prompts and solving them. The interplay encourages evolving curricula (Parker-Holder et al., 2022), potentially benefits both generalization and efficiency (see also § 3.4). Orthogonal to many recent self-play studies in LLM alignment (Choi et al., 2024; Munos et al., 2023; Wu et al., 2024), **eva** is *asymmetric* (Sukhbaatar et al., 2017), with two policies of different goals:

- **Creator**: evolves the prompt distribution for alignment.
- Solver: produces responses and optimizes alignment based on the evolving prompts.

Our main contributions are summarized as:

- A new principle: We propose a generalized **Open-Ended RLHF** objective for aligning language models, which seeks to jointly optimize the prompt distribution and the response policy, thus incentivizes models to self-improve to generalize well on new, unseen tasks beyond the initial training prompt distribution for alignment, as in Definition 1.
- A new algorithm: To optimize the objective, we design a practical algorithm *via* asymmetric self-play, which is implemented through alternating optimization in a **creator-solver game**, and can be easily plugged into any existing alignment pipeline, as in Algorithm 1.
- State-of-the-art performance: We empirically validate **eva** on public alignment benchmarks and present general strong performance improvement when plugged in with different preference optimization algorithms (*i.e.*, DPO, SPPO, SimPO, ORPO). We also conduct extensive ablation studies that provide further insights on choices of informativeness metrics, reward models and training schedules, as in § 4.

eva is easy to implement. We hope it can serve as a scalable method for the research community to build open-ended, robust, and self-improving language agents, that align with human values.

2. Preliminaries

We hereby review major concepts, which we later in § 3 use *regret* and the proxy by *advantage* to identify informative prompts, leading to learning curricular implicitly maximizing *contrastive ratio*.

Alignment by RLHF. Classical RLHF (Ouyang et al., 2022) optimizes on a fixed distribution \mathcal{D} :

$$\max_{\pi_{\theta}} \mathbb{E}_{\mathbf{x} \sim \mathcal{D}, \mathbf{y} \sim \pi_{\theta}(\cdot | \mathbf{x})} \Big[r(\mathbf{x}, \mathbf{y}) \Big] - \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} \Big[\beta \cdot \mathbb{D}_{\mathrm{KL}} \Big[\pi_{\theta}(\mathbf{y} | \mathbf{x}) \parallel \pi_{\mathrm{SFT}}(\mathbf{y} | \mathbf{x}) \Big] \Big],$$
(1)

where **x** and **y** denote the prompts and responses, and $r(\cdot, \cdot)$ is the reward function.

Reward. Let the *optimal policy* of Eq. 1 be $\pi^*(\cdot)$ and $Z(\cdot)$ be the partition function, we have:

$$r(\mathbf{x}, \mathbf{y}) = \beta \cdot \log \frac{\pi^{\star}(\mathbf{y} \mid \mathbf{x})}{\pi_{\text{SFT}}(\mathbf{y} \mid \mathbf{x})} + \beta \cdot \log Z(\mathbf{x}).$$
(2)

Regret and advantage. Given the optimal policy π^* , the *regret* of a policy π_{θ} at **x** is:

$$\operatorname{Regret}(\mathbf{x}, \pi_{\theta}) = \mathbb{E}_{\mathbf{y} \sim \pi^{\star}(\mathbf{y}|\mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \mathbb{E}_{\mathbf{y} \sim \pi_{\theta}(\mathbf{y}|\mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right].$$
(3)

The *advantage* function quantifies how much better a response **y** is w.r.t. a baseline:

$$A(\mathbf{x}, \mathbf{y}) = r(\mathbf{x}, \mathbf{y}) - \mathbb{E}_{\mathbf{y}' \sim \pi(\mathbf{y}' | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}') \right].$$
(4)

Variants of advantage (e.g., the worst-case advantage A_{\min}^{\star}) are related to regret, as shown in Table 2.

Direct preference optimization. The DPO (Rafailov et al., 2023) objective for RLHF is:

$$\mathcal{L}_{\beta}^{\text{DPO}}(\pi_{\theta}) = \sum_{(\mathbf{y}_{+}, \mathbf{y}_{-}, \mathbf{x}) \in \mathcal{D}} - \log \Big[\sigma \big(\beta \cdot \Delta_{\theta; \text{ ref}}^{\mathbf{x}} \big) \Big],$$
(5)

where we use +, - to denote chosen and rejected responses, and denote the contrastive ratio as:

$$\Delta_{\theta; \text{ ref}}^{\mathbf{x}} := \log \frac{\pi_{\theta} \left(\mathbf{y}_{+} \mid \mathbf{x} \right)}{\pi_{\text{ref}} \left(\mathbf{y}_{+} \mid \mathbf{x} \right)} - \log \frac{\pi_{\theta} \left(\mathbf{y}_{-} \mid \mathbf{x} \right)}{\pi_{\text{ref}} \left(\mathbf{y}_{-} \mid \mathbf{x} \right)}.$$
(6)

By reward reparameterization with Eq. 2, variants of advantage also relate to contrastive ratio, as in § 3.4.

3. Method

Algorithm overview. On a high level, **eva** extends classical RLHF to open-ended RLHF *via* a creator that adapts prompt distributions with an easy-to-implement *estimate, sample then evolve* procedure, mimicing the *minimax-regret* policy of asymmetric self-play games, as detailed in §3.3.

Alg	Algorithm 1 eva: Evolving Alignment via Asymmetric Self-Play				
	Input: initial policy π_{θ_0} , initial	prompt set \mathcal{X}_0			
1:	for iteration $t = 1, 2, \dots$ do				
	\triangledown /* creator step */				
2:	estimate informativeness: sample subset:	$\begin{split} & \mathcal{X}_{t-1} \gets \{(\mathbf{x}_i, \texttt{info}(\mathbf{x}_i)) \mid \mathbf{x}_i \in \mathcal{X}_{t-1}\} \\ & \mathcal{X}_{t-1}^{\texttt{info}} \gets \texttt{sample}(\mathcal{X}_{t-1}) \end{split}$			
	self-evolve prompts:	$X_t \leftarrow \texttt{evolve}(X_{t-1}^{\texttt{info}})$			
Э.	▽ /* solver step */	$\forall u \in Y$ generate $(u^{(j)}) = (+u)$			
3:	annotate rewards:	$ \begin{array}{l} \forall \ \mathbf{x}_i \in \mathcal{X}_t, \text{ generate } \{\mathbf{y}_i^{(j)}\} \sim \pi_{\boldsymbol{\theta}_{t-1}}(\cdot \mid \mathbf{x}_i) \\ \mathcal{X}_t' \leftarrow \mathcal{X}_t \cup \{(\mathbf{y}_i^{(j)}, r_i^{(j)})\} \end{array} $			
	preference optimization:	$\boldsymbol{\theta}_t \leftarrow \boldsymbol{\theta}_{t-1} - \eta \nabla_{\boldsymbol{\theta}} \mathcal{L}_{\mathcal{X}_t'}(\boldsymbol{\theta})$			
4: 5:	end for return final solver policy $\pi_{\boldsymbol{\theta}_T}$				

Section overview. We aim to develop language models that can *self-improve to generalize well on new, unseen tasks* beyond the initial training prompt distribution. In § 3.1, we show the limitations of classical RLHF and generalize it to the new objective of open-ended RLHF. In § 3.2, we introduce creator-solver games to tractably achieve the objective. In § 3.3, we detail a practical algorithm with a plug-in creator, compatible with any preference optimization algorithm as the solver. Lastly in § 3.4, we discuss various interpretations for **eva**.

3.1. The Principle: Open-Ended RLHF for Joint Self-Improvement

Intuition. Classical RLHF (*cf.*, Eq. 1) optimizes over a *static* prompt distribution, meaning that the agent is only aligned to a fixed prompt set \mathcal{D} , making it brittle when it is evaluated on new problems from the ever-changing real world. Our Open-Ended RLHF breaks away from this static framework, with the goal to develop an agent that *generalizes* well across *unseen*, *novel* environments (where the tasks entailed in prompts may not have been explicitly encountered during training). To achieve this, we must design a new objective that agents can generate its own problems for self-improvement.

Formalization. We introduce an *open-ended* reference distribution $p_{ref}(\mathbf{x})$, which is conceptually approached by a prompt policy $\pi_{\phi}(\mathbf{x})$, co-evolving with the response policy for alignment:

Definition 1 (Open-Ended RLHF). We define evolving alignment as the open-ended joint optimization on the prompt and response policy for alignment w.r.t the joint reference policy:

$$\max_{\boldsymbol{\phi},\boldsymbol{\theta}} \mathbb{E}_{\mathbf{x} \sim \pi_{\boldsymbol{\phi}}(\cdot), \ \mathbf{y} \sim \pi_{\boldsymbol{\theta}}(\cdot | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \beta \cdot \mathbb{D}_{KL} \left[\pi_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mathbf{x}, \mathbf{y}) \parallel \pi_{ref}(\mathbf{x}, \mathbf{y}) \right], \tag{7}$$

where $\pi_{\phi,\theta}(\mathbf{x}, \mathbf{y}) := \pi_{\phi}(\mathbf{x}) \cdot \pi_{\theta}(\mathbf{y} \mid \mathbf{x})$ and $\pi_{ref}(\mathbf{x}, \mathbf{y}) := p_{ref}(\mathbf{x}) \cdot \pi_{SFT}(\mathbf{y} \mid \mathbf{x})^a$.

$$\max_{\boldsymbol{\phi},\boldsymbol{\theta}} \mathbb{E}_{\mathbf{X} \sim \pi_{\boldsymbol{\theta}}(\cdot)} \left[\mathbb{E}_{\mathbf{Y} \sim \pi_{\boldsymbol{\theta}}(\cdot)} [r(\mathbf{x}, \mathbf{y})] - \beta_1 \mathbb{D}_{\mathrm{KL}} [\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \parallel \pi_{\mathrm{SFT}}(\mathbf{y} \mid \mathbf{x})] - \beta_2 \mathbb{D}_{\mathrm{KL}} [\pi_{\boldsymbol{\phi}}(\mathbf{x}) \parallel p_{\mathrm{ref}}(\mathbf{x})] \right].$$
(8)

Here, $p_{ref}(\mathbf{x})$ represents an *underspecified*, potentially intractable probability distribution over possible tasks (instantiated *via* prompts) in the wild, as a realizable **open-ended reference** that covers the full diversity and complexity of tasks agents may encounter, *not* the initial static prompt set \mathcal{D} . The joint regularization towards $\pi_{ref}(\mathbf{x}, \mathbf{y})$ captures the objective for agents to generalize on alignment in $p_{ref}(\mathbf{x})$ with broader open-ended prompts, while being close to the SFT policy $\pi_{SFT}(\mathbf{y}|\mathbf{x})$.

3.2. The Mechanism: Asymmetric Self-Play via Creator-Solver Games

Intuition. It can be hard to directly solve Eq. 7, due to (i) the **intractability** of the underspecified reference (Dennis et al., 2020), (ii) the **instability** of joint differentiation (Goodfellow et al., 2014). We present a heuristic of iterative alternating optimization by casting it as an **asymmetric creator-solver game**, that **implicitly achieves** the conceptual probability matching of $\mathbb{D}_{\text{KL}}[\pi_{\phi}(\mathbf{x}) \parallel p_{\text{ref}}(\mathbf{x})]$ by iteratively creating a *sequence* of prompt distributions to expand over the task space.

- **Creator** : the prompt player $\pi_{\phi}(\mathbf{x})$ that strategically generate new prompt distributions.
- Solver : the response player $\pi_{\theta}(\mathbf{y} \mid \mathbf{x})$ that learns to optimize for preference alignment.

This game serves as one potential choice to implicitly achieve the Open-Ended RLHF principle.

- By design, the creator can guide the solver with an *informative prompt curriculum*, for it to develop more general capabilities to handle complexities in the wild (Jiang, 2023).
- Intuitively, this resembles RL optimization *via* expectation-maximization (Dayan and Hinton, 1997; Singh et al., 2023), where ϕ for the prompt distribution is fixed at each step.

Formalization. We consider the *minimax regret* strategy (Savage, 1951), where the solver minimizes and the creator maximizes regret², *i.e.*, the reward difference of the current and KL-optimal policy:

$$\operatorname{Regret}(\pi_{\phi}, \pi_{\theta}) = \mathbb{E}_{\mathbf{x} \sim \pi_{\phi}(\cdot)} \Big[\mathbb{E}_{\mathbf{y} \sim \pi_{\theta}(\mathbf{y}|\mathbf{x})} \big[r(\mathbf{x}, \mathbf{y}) \big] - \mathbb{E}_{\mathbf{y} \sim \pi_{\operatorname{KL}}^{\star}(\mathbf{y}|\mathbf{x})} \big[r(\mathbf{x}, \mathbf{y}) \big] \Big].$$
(9)

At the equilibrium (Nash et al., 1950), prior works (Dennis et al., 2020) have shown:

²Please see § H and Eq. 14 for details on the KL-optimal policy $\pi_{\text{KL}}^{\star}(\mathbf{y} \mid \mathbf{x})$.

Remark 1 (Minimax Regret). *If the above solver-creator game reaches an equilibrium, the solver follows a minimax regret policy, i.e., the worst-case regret is bounded:*

$$\pi_{\mathcal{Y}|\mathcal{X}}^{\star} \in \underset{\pi_{\mathcal{Y}|\mathcal{X}}}{\operatorname{arg\,min}} \max_{\pi_{\mathcal{X}}} \mathbb{E}_{\mathbf{x} \sim \pi_{\mathcal{X}}} \left[\operatorname{Regret}(\mathbf{x}, \pi_{\mathcal{Y}|\mathcal{X}}) \right].$$
(10)

To illustrate, open-ended RLHF allows for the creation of evolving prompt distributions that challenge the agent progressively for better generalization; the introduced minimax regret objective further adds *robustness* on top of such evolving curricula by *incentivizing agents to perform well in all cases*.

However, while it is often straightforward for the **solver** to minimize the regret (*e.g.*, by direct policy optimization), the optimal policy remains unknown during optimization, thus regret as the decision signal is often intractable to the **creator** – regret approximation is needed. We design the proxy below for creator's regret approximation (see § H for further illustration), also as a metric for prompt informativeness:

Definition 2 (Informativeness). We estimate the informativeness of a prompt \mathbf{x} in preference optimization by the (absolute) worst-case optimal advantage, approximating regret in Eq. 3:

$$\hat{\text{Regret}}(\mathbf{x}, \pi_{\theta}) | \leftarrow info_{\theta}(\mathbf{x}) := r(\mathbf{x}, \mathbf{y}_{+}) - r(\mathbf{x}, \mathbf{y}_{-}), \tag{11}$$

where

 $\mathbf{y}_{+} := \arg \max_{\mathbf{v}_{i}} r(\mathbf{x}, \mathbf{y}), \quad \mathbf{y}_{-} := \arg \min_{\mathbf{v}_{i}} r(\mathbf{x}, \mathbf{y}), \tag{12}$

and $\{\mathbf{y}_i\}_{i=1}$ is a set of responses sampled from $\pi_{\boldsymbol{\theta}}(\cdot \mid \mathbf{x})$ and $r(\cdot, \cdot)$ is the reward oracle.

We use the informativeness proxy to guide the creator for prompt distribution adaptation, which has a few useful properties under different interpretations, as in § 3.4. In this way, we define a mechanism that the solver learns to improve, as the creator keeps challenging the solver on its weaknesses.

3.3. The Practical Algorithm

We now illustrate eva of Algorithm 1, with practical implementations specified in § A.

3.3.1. The Creator Step: Estimate, Sample then Evolve

Plainly, the creator finds most useful prompts and generate variants of them for preference optimization. One may relate this to *evolution strategies* (Schwefel, 1977) which find the most promising species, then mutate and crossover, or to *curriculum RL* (Parker-Holder et al., 2022) which finds environments with high-regret levels, then edits within some distance. In this work, we do not seek a differentiable creator in this work; the creator is implemented in three steps as in Figure 3 to approximate regret maximization. See more in § H.

Step 1: $info(\cdot)$ – *estimate the informativeness*. For each **x** in the prompt set X_t , we generate responses, annotate rewards and estimate a informativeness metric to **x** by Eq. 11 (see also Table 2).

Step 2: sample(·) – weighted sampling for an informative subset. By using the informativeness metric as the weight, we sample an informative prompt subset X_t^{info} to be evolved later. This is similar to finding high-regret levels in curriculum RL (Parker-Holder et al., 2022).

Step 3: evolve(·) – evolving for a proximal region of high-advantage prompts. Our algorithm is agnostic to and does not rely on any specific evolving method (see empirical evidence in § D.1). We take EvolInstruct (Xu et al., 2023a) as a default off-the-shelf method, which conducts in-depth (*i.e.*, adding constraints, deepening, concretising, complicating) and in-breadth evolving (*i.e.*, mutation) for prompts. Specifically, we iterate over each prompt in the X_t^{into} , where each one is evolved to multiple variations, then optionally mix the newly generated prompts with a uniformly sampled buffer from X_t to create X_{t+1} .

3.3.2. The Solver Step: Solve then Optimize

This step is the classical preference optimization (Rafailov et al., 2023), where responses are generated and the gradient descent is performed. Take the pointwise reward model setting as an example, for every prompt, we sample n responses with reward annotated for each; we take the responses with the maximal and the minimal reward to construct the preference pairs, then optimize upon. This implicitly minimizes the regret to the KL-optimal policy, which we present in more details at § H.

Put together, **eva** can unify existing iterative optimization pipeline (Tran et al., 2023) with a new creator module, which can either share the same network as the solver policy or operate independently.

3.4. Understanding the Informativeness Proxy in Different Intuitive Ways

Learning potential. Our metric intuitively identifies the learning potential of a prompt by measuring the gap between the best and worst response to it from the solver. We reason, that prompts eliciting *both* high-reward and low-reward outcomes, reflect *learnable* tasks where the model is capable of improving but has not yet mastered, thereby implying learning potential (*cf.*, Jiang et al. (2021b)).

Worst-case guarantees. The minimax-regret objective, by design, leads to solvers that perform robustly across the prompt space, thus gives the worst-case guarantee. While exact equilibrium may not be attainable with approximation, our empirical results in § 4.2.1 demonstrate robustness.

Auto-curricula for the players. We visualize the curriculum induced by **eva** in § E. With the stochastic policy, the advantage may be heuristically understood as the reward difference between *a base solver* and *a reference solver*. Rather than optimizing separate solvers (Dennis et al., 2020), we sample multiple times from the same policy to create the pair. In this way, the creator is incentivized to produce new prompts that are just out of the comfort zone of solvers (Chaiklin et al., 2003):

- For overly challenging prompts, both solutions perform poorly, leading to a low proxy.
- For overly easy prompts, the base solution already performs well, again giving a low proxy.
- The optimal strategy is to find prompts that are just beyond the solver's current capability.

Auto-curricula inherent to Contrastive Optimization. Contrastive preference optimization generalizes DPO and a family of algorithms (*c.f.*, Hejna et al. (2023); Rafailov et al. (2023); Tang et al. (2024)), many of whose losses monotonically decrease as the contrastive ratio increases. Here, by Eq. 2 and Eq. 6, the *contrastive ratio* can be written via the *advantage-based proxy*:

$$A_{\min}^{\star}(\mathbf{x}) = \beta \cdot \Delta_{\theta^{\star}: \text{ ref}}^{\mathbf{x}}.$$
 (13)

By our proxy, we implicitly incentivize the creator to generate prompts that *bring the most contrastive responses*, which decrease the loss the most. This matches the curriculum learning literature, which prioritizes (in **eva**, *generatively* prioritizes) examples with smaller losses for better convergence and generalization (Bengio et al., 2009). We hence suggest the *Contrastive Curriculum Hypothesis*: in contrastive preference optimization, prioritizing prompts with higher contrastive ratio improves sample efficiency and generalization. We show initial empirical results on this in § 4.2.1 and § 4.2.4.

4. Experiments

Datasets and models for training. We use **UltraFeedback** (Cui et al., 2023) as the training dataset, which contains diverse high-quality prompts that are primarily human-generated. We use the instruction-finetuned GEMMA-2-9B (Team et al., 2024) as the primary model, which is a strong baseline for models of its size. Detailed experimental setting can be found in § A.

Evaluation settings. We choose: (i) **AlpacaEval 2.0** (Dubois et al., 2024), which assesses general instruction following with 805 questions; (ii) **MT-Bench** (Zheng et al., 2023), which evaluates multi-turn instruction following with 80 hard questions in 8 categories; (iii) **Arena-Hard** (Li et al., 2024b), which is derived from 200K user queries on Chatbot Arena with 500 challenging prompts across 250 topics. We use gpt-4-1106 as the judge and gpt-4-0314 as the baseline for win rate.

Optimization algorithms. We focus on direct preference optimization and consider the following:

- With reference policy: DPO (Rafailov et al., 2023), SPPO (Wu et al., 2024).
- Without reference policy: SimPO (Meng et al., 2024), ORPO (Hong et al., 2024).

Reward models as preference oracles. We use ARMORM-8B (Wang et al., 2024) as our default reward model as the human-preference proxy, and consider the following for ablation studies:

- Pointwise: ARMORM-8B (Wang et al., 2024), SKYWORKRM-27B (Liu and Zeng, 2024).
- Pairwise: PAIRRM-0.4B (Jiang et al., 2023), PAIRRM-8B (Dong et al., 2024).

4.1. Main Results

In general, **eva** brings notable gains in alignment without relying on any human-crafted data, thus offering more efficiency. In the base setup, building on the one-iteration finetuned model ($\theta_{0\to1}$), **eva** adds a creator to self-evolve the prompt set of the initial iteration and uses any preference optimization algorithm for an additional open-ended RLHF iteration, resulting in $\theta_{1\to\tilde{1}}^3$.

eva achieves self-improvement. As shown in red rows in Table 1, **eva** yields notable performance improvement over $\theta_{0\rightarrow 1}$ across different optimization algorithms, especially on the harder Arena-Hard benchmark, which is recognized to be more challenging and distinguishable among others due to the complexity of its prompts and its fairer scoring system (Li et al., 2024b; Meng et al., 2024). Specifically, **eva** brings 8.4% gain with SimPO as the solver, and 8.5% gain with DPO as the solver, surpassing its 27B version and matching claude-3-opus-240229 as reported on the AH leaderboard, while using fully self-automated prompt generation for alignment. Interestingly, **eva** brings the least gains on AlpacaEval 2.0, a simpler evaluation benchmark. This indicates **eva** improves the most for challenging tasks.

eva can surpass human-crafted prompts. We further show that **eva**-prompt-trained models $(\theta_{1\to\hat{1}})$ can match and even outperform those trained on additional new prompts from UltraFeedback $(\theta_{1\to\hat{2}})$ (which we denoted as human prompts), while being much cheaper and more efficient. Additionally, on MT-Bench, training with new human prompts typically show decreased performance in the first turn and only modest gains in the second turn. In contrast, **eva** notably enhances second-turn performance. We hypothesize that **eva** evolves novel, learnable prompts that include characteristics of second-turn questions, reflecting emergent skills like handling follow-up interactions.

Model Family (\rightarrow)			G емма-	2-9В-іт		
Benchmark (\rightarrow)	Arena-Hard		MT-Bench	AlpacaEval 2.0		
Method (\downarrow) / Metric (\rightarrow)	WR (%)	avg. score	1 st turn	2 nd turn	LC-WR (%)	WR (%)
$\overline{\boldsymbol{\theta}_0: \text{SFT}}$	41.3	8.57	8.81	8.32	47.11	38.39
$\overline{\boldsymbol{\theta}_{0 \to 1}}$: DPO	51.6	8.66	9.01	8.32	55.01	51.68
$ heta_{1 ightarrow ilde{1}}$: + eva	60.1 (+8.5)	8.90	9.04	8.75 (+0.43)	55.35	55.53
$ heta_{1 ightarrow 2}$: + new human prompts	59.8	8.64	8.88	8.39	55.74	56.15
$\theta_{0 \rightarrow 1}$: SPPO	55.7	8.62	9.03	8.21	51.58	42.17
$ heta_{1 ightarrow ilde{1}}$: + eva	58.9 (+3.2)	8.78	9.11	8.45 (+0.24)	51.86	43.04
$ heta_{1 ightarrow 2}$: + new human prompts	57.7	8.64	8.90	8.39	51.78	42.98
$\overline{\theta_{0\to 1}}$: SimPO	52.3	8.69	9.03	8.35	54.29	52.05
$ heta_{1 ightarrow ilde{1}}$: + eva	60.7 (+8.4)	8.92	9.08	8.77 (+0.42)	55.85	55.92
$ heta_{1 ightarrow 2}$: + new human prompts	54.6	8.76	9.00	8.52	54.40	55.72
$\overline{\boldsymbol{\theta}_{0 \to 1}}$: ORPO	54.8	8.67	9.04	8.30	52.17	49.50
$ heta_{1 ightarrow ilde{1}}$: + eva	60.3 (+5.5)	8.89	9.07	8.71 (+0.41)	54.39	50.88
$ heta_{1 ightarrow 2}$: + new human prompts	57.2	8.74	9.01	8.47	54.00	51.21

Table 1 | **Main results.** Our **eva** achieves notable alignment gains and can surpass human prompts on major benchmarks across a variety of representative direct preference optimization algorithms.

4.2. Ablation Studies

- - -

_ . .

We conduct in-depth ablation studies on eva, with findings below to be elaborated on later:

- § 4.2.1 informativeness metric: our *regret*-based metric outperforms other alternatives.
- § 4.2.2 sample-then-evolve procedure: our method outperforms greedy selection.
- § 4.2.3 scaling w/ reward models: the alignment gain of eva scales with reward models.
- § 4.2.4 **continual training** : our method has monotonic gain with incremental training; the *evolved data and schedule* by **eva** serves as an *implicit regularizer* for better local minima.

4.2.1.	The Choice	of Informativeness	Metrics:	info(· .)
1.77.1.	The unotee	oj mgormanico	111001 1001	TUT 0 (

Metric	info(x)	Related Approximation		
A_{\min}^{\star} : worst-case optimal advantage	$ \min_{\mathbf{y}} r(\mathbf{x}, \mathbf{y}) - \max_{\mathbf{y}'} r(\mathbf{x}, \mathbf{y}') $	minimax regret (Savage, 1951)		
A^{\star}_{avg} : average optimal advantage	$\left \frac{1}{N}\sum_{\mathbf{y}}r(\mathbf{x},\mathbf{y})-\max_{\mathbf{y}'}r(\mathbf{x},\mathbf{y}')\right $	Bayesian regret (Banos, 1968)		
A_{dts}^{\star} : dueling optimal advantage	$ \max_{\mathbf{y}\neq\mathbf{y}^{\star}} r(\mathbf{x},\mathbf{y}) - \max_{\mathbf{y}'} r(\mathbf{x},\mathbf{y}') $	min-margin regret (Wu and Liu, 2016)		

Table 2	The reward-advantage-based	metrics that serve as the inf	ormativeness proxies for prompts.

Benchmark (\rightarrow) Method (\downarrow) / Metric (\rightarrow)		Arena-Hard	d MT-Bench			AlpacaEval 2.0		
		WR (%)	avg. score	1 st turn	2 nd turn	LC-WR (%)	WR (%)	
$\overline{oldsymbol{ heta}_{0 ightarrow 1}}$: [OPO	51.6	8.66	9.01	8.32	55.01	51.68	
$\theta_{1 \rightarrow \tilde{1}}$:	+ eva (uniform)	57.5	8.71	9.02	8.40	53.43	53.98	
$egin{aligned} & m{ heta}_{1 ightarrow ilde{1}}: \ & m{ heta}_{1 ightarrow ilde{1}}: \ & m{ heta}_{1 ightarrow ilde{1}}: \ & m{ heta}_{1 ightarrow ilde{1}}: \end{aligned}$	+ eva (var(r)) + eva (avg(r)) + eva (1/avg(r))	54.8 58.5 56.7	8.66 8.76 8.79	9.13 9.13 9.13	8.20 8.40 8.45	54.58 55.01 55.04	52.55 55.47 54.97	
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$:	+ eva $(1/A_{\min}^{\star})$	52.3	8.64	8.96	8.31	53.84	52.92	
$egin{aligned} & m{ heta}_{1 ightarrow ilde{1}}: \ & m{ heta}_{1 ightarrow ilde{1}}: \end{aligned}$	+ eva (A_{avg}^{\star}) (our variant) + eva (A_{dts}^{\star}) (our variant)	60.0 60.0	8.85 8.86	9.08 9.18	8.61 8.52	56.01 55.96	56.46 56.09	
$\theta_{1 \rightarrow \tilde{1}}$:	+ eva (A^{\star}_{\min}) (our default)	60.1 (+8.5)	8.90	9.04	8.75 (+0.43)	55.35	55.53	

Table 3 | **Choice of informativeness metric matters.** Our metric by *advantage* achieves the best performances, comparing with others as weights to sample for evolving. See also $\S F$ for visualization.

Advantage as the informativeness metric outperforms baselines. As in Table 3, eva offers an effective curriculum by the advantage-based proxy as the informativeness metric (bottom row):

- *Comparing w/ uniform evolving* (brown): Existing baselines generate prompts in a uniform manner (Yuan et al., 2024) (*cf.*, the principle of insufficient reason (Keynes, 1921; Tobin et al., 2017)). **eva** concretely outperforms, corroborating Das et al. (2024) that uniform learners can suffer from sub-optimality gaps.
- *Comparing w/ other heuristics* (blue): Prior practices (Team et al., 2023) tried heuristics like prioritizing prompts w/ the most variance in its rewards or w/ the lowest/highest average. We find our advantage based methods (red) outperforms those heuristics; see § F for more.
- *Comparing w/ the inverse advantage* (purple): Contrary to curriculum learning, a line of works conjecture that examples w/ higher losses may be prioritized (Jiang et al., 2019; Kawaguchi and Lu, 2020), which can be done by inverting our metric. We find it significantly *hurt* the alignment gain, corroborating Mindermann et al. (2022) that those examples can be unlearnable or irrelevant, meaning our curriculum is effective and practical.
- Among our advantage variants (green): We designed variants of our default advantage-based metric, as in Table 2; the default A^{*}_{min} remains competitive among its peers. Together, the advantage-based principle provides a robust guideline for prompt sampling and evolving.

The lesson is that we must be selective about which are the promising to evolve, otherwise unlearnable, noisy or naïve prompts may hinder learning. Our regret-inspired metric represents a solid baseline.

Benchmark (\rightarrow) Method (\downarrow) / Metric (\rightarrow)		Arena-Hard	MT-Bench			AlpacaEval 2.0		
		WR (%)	avg. score	1 st turn	2 nd turn	LC-WR (%)	WR (%)	
$\overline{oldsymbol{ heta}}_{0 ightarrow 1}$: D	PPO	51.6	8.66	9.01	8.32	55.01	51.68	
$\overline{\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}}$:	[no evolve]-greedy	56.1	8.68	8.98	8.38	54.11	53.66	
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$:	[no evolve]-sample	55.3	8.69	9.00	8.38	54.22	54.16	
$\theta_{1 \rightarrow \tilde{1}}$:	+ eva-greedy (our variant)	59.5	8.72	9.06	8.36	54.52	55.22	
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$:	+ eva-sample (our default)	60.1	8.90	9.04	8.75	55.35	55.53	

4.2.2. The Effect of the Sample-then-Evolve Procedure

Table 4 | **Effect of evolving.** The blue are those training w/ only the informative subset and w/o evolving); we denote <code>-sample</code> for the default weighted sampling procedure in Algo 1, while using <code>-greedy</code> for the variant from the classical active data selection procedure (*cf.*, a recent work (Muldrew et al., 2024) and a pre-LLM work (Kawaguchi and Lu, 2020)), which selects data by a high-to-low ranking via the metric greedily. We show evolving brings a remarkable alignment gain (the red v.s. the blue); and as we evolve, sampling is more robust than being greedy (*cf.*, Russo et al. (2018)).

The design of evolve (·) in eva is effective. As in Table 4, we show:

- Removing the evolve(·) step: if we only do subset sampling or ordered selection, we still have gain, but not as much as w/ evolving (*e.g.*, **eva** brings 4.8% additional wins on AH).
- Altering the sample(·) step: if we greedily select prompts by the metric instead of using them as weights for importance sampling, the performance will be weaker as we evolve.

This shows that simply adaptive training within a fixed prompt distribution is unsatisfactory; our open-ended RLHF with *generative* prompt exploration gives a substantial headroom for self-improvement.

4.2.3. Scaling Pointwise and Pairwise Reward Models



Figure 4 | **eva scales with quality of reward models**, under pointwise RMs w/ DPO (*left*) and pairwise RMs w/ SPPO (*right*). Note SPPO handles general preferences thus requires pairwise RMs, and DPO relies on the Bradley-Terry assumption, for which pointwise RMs are suitable. Figure 4 presents the length-controlled win rate of **eva** on AlpacaEval using pointwise and pairwise reward models of varying scales. The results give a clear trend: as the quality of reward models improve, **eva** brings higher alignment gain. The scaling observation shows the effectiveness of **eva** in exploiting more accurate reward signals to choose informative prompts for better alignment. One takeaway is interaction w/ the external world is essential for intelligence. The more accurate reward signals observed, the better the agent incentivize themself to improve (*cf.*, Silver et al. (2021)).

4.2.4. eva Improves Both Sample Efficiency and Generalization

We continuously run the default *incremental training* (*i.e.*, trainining from the last checkpoint w/ the evolved set in each iteration), as in Fig 5 and § D.2, **eva** presents *monotonic performance gain* over iterations, and surpasses that trained w/ new human prompts, implying the generalization benefit.

We conjecture that behaviors of the dashed/dotted lines relate to *loss of plasticity* (Abbas et al., 2023; Ash and Adams, 2019; Dohare et al., 2023; Nikishin et al., 2022; Xue et al., 2024). Classical works resolve it by the *optimization* perspective (*e.g.*, weight perturbing), whereas **eva** provides a new *data* perspective, potentially mimicing an **implicit regularizer for better generalization**.



Figure 5 | **Continual training**. **eva** stays robust w/ more iterations in incremental training.

The solutions found by **eva** cannot be recovered by training longer w/ a fixed distribution (the dashed), nor by naïvely sourcing new prompts w/o examining informativeness (the gray dotted), thus our generative data schedule is effective.

In Table 5, we ablate **eva** in *scratch training*, *i.e.*, training w/ the full set (the evolved and the original data). **eva** is competitive in incremental training, thus *learns more effective* with *less data* – a nice bonus via minimax regret (Jiang et al., 2021a).

Benchmark (→)		Arena-Hard MT-Bench		AlpacaEval 2.0	
Method (\downarrow) / Metric (\rightarrow)		WR (%)	avg. score	LC-WR (%)	
θ_0 : SFT	[41.3	8.57	47.11	
$\overline{\boldsymbol{\theta}_{0 \rightarrow 1}}$: I	OPO	51.6	8.66	55.01	
$\boldsymbol{\theta}_{0 \rightarrow \tilde{1}}$:	eva (scratch)	59.8	8.88	54.59	
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$:	eva (incremental)	60.1	8.90	55.35	

Table 5 | Ablation on incremental v.s. scratch training.

5. Related Works

Self-improving algorithms and iterative optimization. This line of work focuses on iteratively generating samples from the response policy and continuously re-training the policy by selected self-generated samples. Major works include ReST (Gulcehre et al., 2023; Singh et al., 2023), STaR (Zelikman et al., 2022), RFT (Yuan et al., 2023), RAFT (Dong et al., 2023), self-improving LLMs (Huang et al., 2022; Yuan et al., 2024); in the context of preference optimization, iterative DPO (Pang et al., 2024; Tajwar et al., 2024; Tran et al., 2023; Xiong et al., 2024; Xu et al., 2023b) has proven effective. Most works focus on self-training by improving in $\mathcal{Y} \mid X$, while we *jointly optimize* both responses and prompts via generative exploration in the (X, \mathcal{Y}) space. Among them, we also distinctly present a game-theoretic framework for continual training.

Prompt synthesis for language models. Existing works include Self-Instruct (Wang et al., 2022), WizardLM (Luo et al., 2023; Xu et al., 2023a), Self-Align (Sun et al., 2024), Glan (Li et al., 2024a), EvoPrompt (Guo et al., 2023), Magpie (Xu et al., 2024) and others (Long et al., 2024). **eva** is an orthogonal contribution since any synthesis method can be plugged in as the $evolve(\cdot)$ for the creator. Importantly, our work presents a new reward-related metric to endow prompt the notion of informativeness. We also focus on preference optimization algorithms, while those existing works primarily use synthesized prompts in an SFT-only way.

Self-play and curriculum RL. Agents trained on a fixed data distribution are often brittle and may struggle to adapt to the real world (Hughes et al., 2024a). Self-play (Goodfellow et al., 2014; Samuel, 1959; Silver et al., 2016) addresses this by having the agent learn through self-interaction, thus creating more diverse experiences and automatic curricula. In asymmetric self-play, the paradigm centers on "*Alice proposing a task, and Bob doing it*" (Beukman et al., 2024a; Dennis et al., 2020; Samvelyan et al., 2023; Sukhbaatar et al., 2017). We revive the classical asymmetric self-play (Sutton et al., 2011) in optimizing language models. Unlike traditional curriculum RL (Parker-Holder et al., 2022), which renders environments by specifying levels (Dennis et al., 2020), our approach is *generative* by nature, as we directly generate *states* from auto-regressive language models. We believe such generative exploration in the joint state-action space presents a new training paradigm.

Self-play in RLHF. A growing line of research frames RLHF as a *symmetric* self-play game, where both players are response players (Choi et al., 2024; Munos et al., 2023; Rosset et al., 2024; Wu et al., 2024). However, these methods still rely on a fixed prompt distribution thus is sub-optimal. In contrast, we solve this by *asymmetric* self-play, enabling evolving prompt distributions for more generalizable language agents. During our work, we notice one concurrent paper adopting the asymmetric two-player setup (Zheng et al., 2024), however (i) it applies to adversarial attack tasks instead of general alignment benchmarks, (ii) it is incompatible w/ direct preference optimization, and (iii) it relies on the maxmin principle (which may produce unlearnable environments (Dennis et al., 2020)) instead of the minimax *regret* principle (Fan, 1953; Savage, 1951) as we do. We also first precisely define the new problem of open-ended RLHF, generalizing over classical RLHF.

6. Concluding Remarks

Future directions. eva defines a new paradigm for reinforcement learning from human feedback, opening up many new directions, *e.g.*, (i) extending to differentiable creator policies, combining w/ other $evolve(\cdot)$ methods; (ii) evolving for more iterations w/ on-policy solvers like RLOO (Ahmadian et al., 2024); (iii) investigating exploration bonuses for distribution diversity and coverage, and the self-consuming loop (Gerstgrasser et al., 2024); (iv) extending the game with more modality (Bruce et al., 2024), and/or with more players for full automation (*e.g.*, rewarders, critics, rewriters, verifiers, retrievers); (v) extending from alignment to reasoning (*e.g.*, auto-conjecturing for theorem proving (Poesia et al., 2024) can be cast as an asymmetric game), or from the bandits to the trajectories w/ process reward models and hierarchical search for creator and solver generations; (vii) further scaling up w/ millions of prompts with continual RL training (Abel et al., 2024).

Conclusions. eva is a new, simple and scalable framework for aligning language models, and can be plugged into any existing alignment pipeline. The primary takeaway may be that RLHF can be made open-ended: (i) self-evolving joint data distributions can bring significant gain (as shown across various optimization algorithms), and (ii) reward advantage acts as an effective metric informing the collection and creation of *future* prompts for alignment. **eva** presents a new view of alignment by framing it as an asymmetric game between a creator generating *new* and *learnable* states (*i.e.*, prompts) and a solver producing preferred actions (*i.e.*, responses). **eva** also *incentivizes agents to create problems* rather than to simply *solve problems*, which is a key feature of intelligence, yet classical bandit/RL works often neglect.

Acknowledgements

We extend our sincerest gratitude to Bilal Piot for his thoughtful reviews and valuable advice on this paper. We are also grateful to Chenkai Kuang, Dustin Tran, Albert Webson, Hanzhao Lin, Clara Huiyi Hu, Jeremiah Liu, Luheng He, Chenjie Gu, Yong Cheng, Pei Sun, and Heng-Tze Cheng for their fun discussions and notes on Self-Play. We also thank David Abel, Yuxin Chen, Ziniu Hu, Guohao Li, Rylan Schaeffer, Haifeng Xu, Chaoqi Wang and Yifei Wang for their initial helpful discussions and references on fine-tuning, contrastive learning, data synthesis, open-ended learning, and continual reinforcement learning.

Reproducibility Statement

We hope to open-source all the code, datasets (synthesized prompts/responses) and models, *upon approval*. Before then, we are more than happy to provide any clarification requested to help re-implement **eva** and replicate our results. Our code base is made to be simple to use for practitioners, requiring only a creator module addition to the commonly adopted Alignment Handbook pipeline.

Societal Impact

eva enables scalable training of language agents through open-ended training, improving AI alignment with human values, which may ultimately contribute to social welfare (Arrow, 1952; Pigou, 1920; Zhi-Xuan et al., 2024). This could *democratize* the development of more generally capable AI agents, benefiting a wide range of applications from education to scientific discovery.

We recognize that **eva** relies on self-exploration guided by reward signals. If these signals are inaccurate or misaligned, the trained agents may exhibit undesirable behaviors such as reinforcing biased hallucination. Mitigating these risks requires continued research into robust reward models, transparent evaluation protocols, open collaboration within the AI research community, and more. We are committed to supporting these efforts by sharing our findings and implementations to promote open and responsible research and development.

Appendix

The appendix is organized as follows:

- § A Details On Reproducibility
- § B Plug-In Loss Functions Used In Main Results
- § C Extended Results for Experiments in the Main Paper
- § D Additional Experiments
- § H Illustration on Methodology
- § E, § F and § I Illustrations on Prompts, Responses and Relevant Distributions
- § G Additional Literature Review

A. Details on Reproducibility

Our code is built based on many open-source packages, and we sincerely thank every developer and contributor of these projects for their efforts and contributions to the community.

As mentioned, our code base is made to be simple to use for practitioners, requiring **only a creator module addition** within the commonly adopted Alignment Handbook pipeline.

Hyperparameter settings. We follow the original hyperparameter settings as in (Hong et al., 2024; Meng et al., 2024; Wu et al., 2024), default to be:

Hyperparameter (\downarrow) / Loss (\rightarrow)	DPO	ORPO	SimPO	SPPO
learning rate	5e-7	5e-7	8e-7	5e-7
learning rate scheduler	cosine	cosine	cosine	linear
β	0.05	/	10	0.001
γ	/	/	5	/
λ	/	0.5	/	/
no. epochs per iter	2	1	1	6
warmup ratio per iter	0.1	0.1	0.1	0.1
effective batch size	8	8	32	8
max length	2048	2048	2048	1024
max prompt length	1024	1024	1024	512
optimizer	adamw	adamw	adamw	rmsprop

Iterative Training Settings. By default (Tran et al., 2023; Yuan et al., 2024), we train with equal-size prompt subset in each iteration. Unless otherwise specified, we use 10K prompts from the UltraFeedback dataset (Cui et al., 2023) per iteration. The incremental training proceeds as follows:

- θ_0 : Base SFT model.
- $\theta_{0\to 1}$: initialize with θ_0 ; then train with the prompt split X_1 by self-generated responses from the initial model θ_0 .
- *θ*_{1→2}: initialize with *θ*_{0→1}; trained with the prompt split *X*₂ via by self-generated responses from the initial model *θ*_{0→1}.

For evolving prompts (*e.g.*, evolving X_1 to $X_{\tilde{1}}$), with the calculated informativeness metric for each prompt, we normalize them as the weight to do weighted sampling for a 25% informative subset to get X_1^{info} . We then iterate over in X_1^{info} and call EvolInstrut (Xu et al., 2023a) as the plug-in evolving method (with the number of evolutions as 4) using the default mutation templates for (i) in-depth evolving (constraints, deepening, concretizing, increased reasoning steps) and (ii) in-breadth evolving (extrapolation) as implemented in tasks/evol_instruct/utils.py of distilabel==1.3.2. Next we uniformly select 80% prompts from this evolved dataset and 20% from the original dataset (*i.e.*, the buffer) to form $X_{\tilde{1}}$. We do not seek extensive parameter search (*e.g.*, the number of evolutions, the evolving ratio) in this stage and encourage future works on exploring this and other plug-in evolving methods. For solver we generate 6 responses per prompt. We use 42 as the random seed.

Software environments. All experiments are conducted on 8xNVIDIA H100 SXM GPUs. Our codebase primarily relies on transformers==4.40.0. For the response generation of GEMMA models at the training stage, we use vllm==0.5.4 with flashinfer backend for CUDA 12.4 and torch 2.4. For evolving prompts, we use distilabel==1.3.2, and use LiteLLM to serve Gemini (default to be gemini-1.5-pro) and transformers models (default to be gemma-2-9b-it). For evaluation on all benchmarks, we use sglang==0.2.10 and openai==1.35.14, with gpt-4-1106-preview as the judge model and gpt-4-0314-preview as the baseline model. Specifically for AlpacaEval 2.0, we use alpaca_eval_gpt4_turbo_fn as the annotator config.

B. Plug-In Loss Functions Used in Main Results

With Reference Model						
DPO (Rafailov et al., 2023)	$\ell_{\beta}(\pi_{\theta}) = -\log \left[\sigma \left(\beta \cdot \Delta_{\pi_{\theta};\pi_{\text{ref}}}^{\mathbf{x}} \right) \right] := -\log \left[\sigma \left(\beta \cdot \log \frac{\pi_{\theta}(\mathbf{y}_{+} \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_{+} \mathbf{x})} - \beta \cdot \log \frac{\pi_{\theta}(\mathbf{y}_{-} \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_{-} \mathbf{x})} \right) \right]$					
SPPO (Wu et al., 2024)	$\ell_{\beta}(\pi_{\theta}) = -\log\left[\sigma\left(\left(\beta \cdot \log \frac{\pi_{\theta}(\mathbf{y}_{+} \mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_{+} \mathbf{x})} - \frac{1}{2}\right)^{2} + \left(\beta \cdot \log \frac{\pi_{\theta}(\mathbf{y}_{-} \mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_{-} \mathbf{x})} + \frac{1}{2}\right)^{2}\right)\right]$					
	Without Reference Model					
SimPO (Meng et al., 2024)	$\ell_{\beta,\alpha}(\pi_{\theta}) = -\log\left[\sigma\left(\beta \cdot \Delta_{\pi_{\alpha}^{1/ \mathbf{y} };1}^{1} - \alpha\right)\right] := -\log\left[\sigma\left(\frac{\beta}{ \mathbf{y}_{+} }\log\pi_{\theta}(\mathbf{y}_{+} \mathbf{x}) - \frac{\beta}{ \mathbf{y}_{-} }\log\pi_{\theta}(\mathbf{y}_{-} \mathbf{x}) - \alpha\right)\right]$					
ORPO (Hong et al., 2024)	$\ell_{\lambda}(\pi_{\theta}) = -\log\left[\sigma\left(\lambda \cdot \Delta_{\text{odd}_{\theta}(t)}^{\mathbf{x}}\right)\right] := -\log\left[\sigma\left(\lambda \cdot \log \frac{\text{odd}_{\theta}(\mathbf{y}_{+} \mathbf{x})}{\text{odd}_{\theta}(\mathbf{y}_{-} \mathbf{x})}\right)\right], \text{ where } \text{odd}_{\theta} = \frac{\pi_{\theta}}{1-\pi_{\theta}}$					

Table 6 | Direct preference alignment algorithms used in the main experiments. In parameter tuning, we include an additional negative log-likelihood loss for chosen responses (*i.e.*, $\frac{\gamma}{|\mathbf{y}_{+}|} \log \pi_{\theta}(\mathbf{y}_{+}|\mathbf{x})$).

C. Additional Experimental Results for the Main Paper

In general, **eva** maintains the downstream performance and is robust on reasoning-heavy tasks, and the scaling with reward models is more prominent on AlpacaEval, possibly due to training sources for such reward models.

Method (\downarrow) / Dataset (\rightarrow)	MUSR-TA	TruthfulQA-Gen	WMDP	GSM8K	GSM-Plus	MMLU-Pro
θ_0 : SFT	38.80	34.76	58.62	24.64	18.62	52.08
$\overline{\boldsymbol{\theta}_{0 \to 1}}$: DPO	38.40	34.76	58.45	24.56	18.50	52.63
$oldsymbol{ heta}_{1 ightarrow ilde{1}}$: + eva	38.40	34.15	58.40	24.26	17.96	53.03
$\theta_{0\to 1}$: SPPO	40.80	34.15	58.72	24.79	18.42	52.70
$oldsymbol{ heta}_{1 ightarrow ilde{1}}$: + eva	41.20	34.64	58.94	25.40	18.88	52.47

Table 7 | Performance on Downstream tasks.

Benchmark (\rightarrow) Method (\downarrow) / Metric (\rightarrow)		MT-Bench			Arena-Hard	AlpacaEval 2.0			
		avg. score	1 st turn	2 nd turn	WR (%)	LC (%)	WR (%)		
$\theta_{0\rightarrow 1}$: DPO		8.66	9.01	8.32	51.6	55.01	51.68		
$\boldsymbol{\theta}_{1 ightarrow ilde{1}}$: + eva-i	(ArMO-8B)	8.90	9.04	8.75	60.1	55.35	55.53		
$\boldsymbol{\theta}_{1 ightarrow ilde{1}}$: + eva-i	(SkyworkRM-27B)	8.75	9.07	8.43	60.3	56.12	56.40		

Table 8 | Effect of (pointwise) reward models.

Benchmark (\rightarrow)		MT-	Bench		Arena-Hard	Alpacal	Eval 2.0
Method ()) / Metric (\rightarrow)	avg.	score 1 ^s	st turn	2 nd turn	WR (%)	LC (%)	WR (%)
$\theta_{0\to 1}$: SPPO	8.	62	9.03	8.21	55.7	51.58	42.17
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$: + eva-i (PAIRF	RM-0.4B) 8.	78	9.11	8.45	58.9	51.86	43.04
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$: + eva-i (PAIRF	RM-8B) 8.	89	9.08	8.70	60.2	52.71	44.52

Table 9 | Effect of (pairwise) reward models.

D. Additional Experimental Results (as Extensions)

D.1. Experiments on Different evolve(·) Methods

As an addition to Table 1, we have experimented with three different evolve(·) methods, including:

- SelfInstruct (Wang et al., 2022): Given seed prompts, variations are created based on criteria such as verb diversity and style blending (mixing interrogative and imperative styles). Unlike EvoIInstruct (Xu et al., 2023a), which generates prompt variations sequentially, this approach generates independently. We follow the one-shot implementation in self_instruct.py of distilabel==1.4.1 and modified the instruction on conciseness so that those newly generated prompts have similar lengths compared to the seed prompts.
- EvolQuality and EvolComplexity (Liu et al., 2023b): The two methods use the same evolutionary approach (*i.e.*, sequentially generating), but with slightly different meta-instructions for prompt generation, where EvolQuality asks to improve the quality (*i.e.*, helpfulness, relevance, etc) of the seed prompt and EvolComplexity asks to improve the complexity (*i.e.*, increased reasoning steps, etc) of the seed prompt. We follow the implementation in evol_quality/utils.py and evol_complexity/utils.py of distilabel==1.4.1.

Model Family (→)	Gemma-2-9B-it		
Benchmark (\rightarrow)	Arena	-Hard	
Method (\downarrow) / Metric (\rightarrow)	WR (%)	avg. len	
$\overline{\theta_0: \text{SFT}}$	41.3	544	
$\overline{{oldsymbol{ heta}}_{0 ightarrow 1}$: DPO	51.6	651	
$\theta_{1 \rightarrow \tilde{1}}$: + eva (evolve(·) = EvolInstruct)	60.1	733	
$\theta_{1 \to \tilde{1}}$: + eva (evolve(·) = EvolQuality)	58.7	721	
$\theta_{1 \to \tilde{1}}$: + eva (evolve(·) = EvolComplexity)	60.6	749	
$\theta_{1 \rightarrow \tilde{1}}$: + eva (evolve(·) = SelfInstruct)	57.2	725	

Table 10 Iceballe of ability aniel elle elle alle	Table 10	Results	of using	different	evolving	methods.
---	----------	---------	----------	-----------	----------	----------

eva is effective under different evolving methods. As shown in Table 10, our method brings strong performance gain without training with additional human prompts. Among the experimented methods, we find EvolComplexity shows better results.

We believe the main strength of such method is its **simplicity**. Viewing the evolving process as $\mathbf{x}' \leftarrow p_{\theta}(\cdot | \mathbf{x}, \text{meta_prompt})$, one can easily tune the meta prompt in natural language for improved performance. However, such simplicity comes at a price: (i) the main weakness is that the default method does not take **environmental feedback** into account (*e.g.*, rewards received, verbal critique on responses, etc) and relies on the pre-defined meta prompt, thus the evolving may be less directional; we encourage practitioners to consider incorporating more richer feedback during evolving (one way to formulate this is by generative optimization (Cheng et al., 2024; Nie et al., 2024; Yuksekgonul et al., 2024)); (ii) another weakness is that existing method is single-shot (*i.e.*, we evolve based on a single **x** each time), thus the **diversity** of the generation may be limited – we anticipate future works improving this with multi-shot evolving by graph-based sampling. In this regard, the evolving process can be viewed as $\{\mathbf{x}'\}_{i=1}^N \leftarrow p_{\theta}(\cdot | \{\mathbf{x}\}_{i=1}^M, \text{meta_prompt}, \text{env_feedback})$.

D.2. Experiments on Number of Iterations

As an addition to § 4.2.4, we have experimented with the following settings:

- 10K prompts per iteration with 3 iterations.
- 20K prompts per iteration with 3 iterations (*i.e.*, all seed prompts are used).
- 60K prompts per iteration with 2 iterations (*i.e.*, all seed prompts are used).

Due to time constraints, we did not perform an extensive hyper-parameter search; however, we believe the results presented below sufficiently demonstrate the performance gains achieved by **eva**.

Gemma-2-9B-it		
Arena	-Hard	
WR (%)	avg. len	
41.3	544	
51.6	651	
59.8	718	
61.2	802	
60.1	733	
62.0	787	
62.2	774	
	Gемма- Arena- WR (%) 41.3 51.6 59.8 61.2 60.1 62.0 62.2	

Table 11 | Results of using 10k prompts per iteration (DPO + length-penalized NLL loss).

Model Family (\rightarrow)	G емма-	2-9В-іт
Benchmark (\rightarrow)	Arena	-Hard
Method (\downarrow) / Metric (\rightarrow)	WR (%)	avg. len
$\boldsymbol{\theta}_0$: SFT	41.3	544
$\theta_{0\rightarrow 1}$: DPO (20k)	53.2	625
$\boldsymbol{\theta}_{1 \rightarrow 2}$: DPO (20k)	47.0	601
<i>θ</i> _{2→3} : DPO (20k)	46.8	564
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$: + eva (20k)	59.5	826
$\boldsymbol{\theta}_{\tilde{1} \rightarrow \tilde{2}}$: + eva (20k)	60.0	817
$\boldsymbol{\theta}_{\tilde{2} \to \tilde{3}}^{}$: + eva (20k)	61.4	791

Table 12 | Results of using 20k prompts per iteration (DPO + length-penalized NLL loss).

Model Family (\rightarrow)	Gemma-	2-9В-іт
Benchmark (\rightarrow)	Arena	Hard
Method (\downarrow) / Metric (\rightarrow)	WR (%)	avg. len
θ_0 : SFT	41.3	544
$\theta_{0\to 1}$: DPO (60k)	58.9	717
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$: + eva (60k)	59.6	725
$\boldsymbol{\theta}_{\tilde{1} \rightarrow \tilde{1}'}$: + eva (60k)	61.9	792

Table 13 | Results of using 60k prompts per iteration (DPO + length-penalized NLL loss).

eva can bring robust gains with multiple iterations. As shown in Table 11, 12, and 13 below, our method presents persistent performance gain over iterations, and concretely surpasses the performance by default DPO training with true human prompts.

However, there exist diminishing marginal gains in iterative off-policy training. We ground **eva** in the iterative (off-policy) preference alignment paradigm due to its efficiency and ease of integration. However, such paradigms inherently face diminishing returns, where performance gains decrease with successive iterations, as previously observed in (Nikishin et al., 2022; Setlur et al., 2024; Wu et al., 2024; Yuan et al., 2024). While the generative data schedule in **eva** mitigates these challenges and extends beyond default training with human prompts (see also §4.2.4), the gains can weaken over iterations. We summarize potential reasons as: (i) the **off-policy signal decay** – as the number of examples increases, signals from the off-policy data become weaker due to distributional shift; (ii) the **loss of plasticity**, where the agent's ability to learn good policies decreases in continuing training with more iterations (Nikishin et al., 2022); (iii) the **ability of the solver** – as we evolve more harder prompts, it is harder for the solver to produce preferred response (thus more explicit reasoning techniques may be needed); (iv) the **ability of the reward model** to correctly provide reward signals to responses and thus informativeness signals to prompts, as there may exists distributional mismatch.

Thus, we envision future work to build on **eva** by: (i) exploring its integration with **on-policy RLHF** (*e.g.*, instead of evolving prompts in iterations, one may evolve in batches); (ii) **enhancing solver capabilities**, such as sampling more responses during inference or leveraging meta-instructions to guide deeper reasoning; (iii) continual training of reward models for them to co-evolve with the creators and the solvers.

D.2.1. Bonus Experiments on rewriter (·) In The Loop

We present the basic idea here for practitioners to build upon. The motivation comes from the hypotheses derived from § D.2: as the prompts gets harder by evolving, there may be greater demands on the solver's capabilities *compared to earlier iterations*. As such, the solver may not be naively treated the same. One may address this by either scaling up response sampling or introducing meta-instructions to explicitly enhance the solver's reasoning.

We design a proof-of-concept experiment *w.r.t* the latter by adding **rewriter** in **eva**'s solver step. Previously, as in Algo. 1 and § 3.3.2, for each prompt **x**, we generate multiple responses, and choose the best as \mathbf{y}_+ and the worst as \mathbf{y}_- for preference optimization. Now, we add one more rewriting step that attempts to enhance \mathbf{y}_+ to be \mathbf{y}'_+ , by applying a rewriting instruction (Liu et al., 2023b) that asks the solver to alter \mathbf{y}_+ with imporved helpfulness, relevance, reasoning depths, creativity and details while keeping the similar length. We then train with $(\mathbf{x}, \mathbf{y}'_+, \mathbf{y}_-)$ for preference optimization. Table 14 shows that adding the rewriter yields concrete performance gains over the default training method, while keeping the training budget and only slightly increasing cost for offline data generation.

Model Family (\rightarrow)	Gemma-2-9B-it		
Benchmark (\rightarrow)	Arena	-Hard	
Method (\downarrow) / Metric (\rightarrow)	WR (%)	avg. len	
$\overline{\boldsymbol{\theta}_0}$: SFT	41.3	544	
$\overline{\boldsymbol{\theta}_{0\to 1}}$: DPO (10k)	51.6	651	
$\boldsymbol{\theta}_{1 \rightarrow \tilde{1}}$: + eva (10k)	60.1	733	
$\theta_{1 \to \tilde{1}}$: + eva with rewriter (10k)	61.9	741	

Table 14 | Results of adding rewriter in the solver step.

E. Curriculum Visualization Over Iterations

We now present initial observations supporting the intuition in § 3.4, where **eva** brings auto-curricula and the creator is incentivized to create new prompts that are both learnable and worth-learning.



Figure 6 | **Training distributions.** The prompt distribution of Table 11 for evolved prompts by zero-shot classification. **eva** creates a curriculum that prioritizes math / coding prompts over iterations.



Figure 7 | **Benchmark performance.** The radar figure for ratings on MT-Bench (Zheng et al., 2023), where each category contains ten problems. **eva** prioritizes and gradually improves on coding, math and reasoning over iterations, implicitly reflecting a learned curriculum.

E.1. Complexity and Quality of Prompts Over Iterations

Prompt Set (\downarrow) / Metric (\rightarrow)	Complexity (1-5)	Quality (1-5)
UltraFeedback (seed)	2.90	3.18
UltraFeedback- eva -Iter-1	3.84	3.59
UltraFeedback- eva -Iter-2	3.92	3.63
UltraFeedback- eva -Iter-3	3.98	3.73



As in Table 15, there is a gradual improvement of prompt complexity and quality over iterations with **eva**. We sample 10K prompts per iteration, and use the below prompts modified from Liu et al. (2023b) for the complexity and quality evaluation, with gemini-1.5-flash as the scorer:

> Rank the following questions according to their **quality**. Your evaluation should consider the below factors: Helpfulness, Relevance, Accuracy, Depth, Creativity, and Level of detail. Score each response from 1 to 5: 1: Poor quality, 2: Below average, 3: Average, 4: Good, 5: Excellent.

> Rank the following questions according to their difficulty and complexity. Use a fixed scoring system: 1: Very simple, 2: Simple, 3: Moderate, 4: Difficult, 5: Very difficult.

F. Visualization on Prompt Selection Metric



Figure 8 | The probability density distributions of informativeness metrics compared in Table 3 – they show different patterns.



Figure 9 | The correlation plot for reward advantage (ours) and reward variance – they are only *weakly* correlated.

In **eva**, we assign each prompt an informativeness value, which the creator will use as the weight to sample from the seed prompts for prompt synthesis. In § 4.2.1, we have shown that traditional methods like reward mean and reward variance are less effective as our advantage-based informativeness proxy. The intuition is simple: advantage/regret-based proxy aligns better with the preference optimization objective. We here further illustrate that they are statistically different from other choices:

- Figure 8: The distribution of informativeness values shows that reward variance is heavily concentrated at lower values, reward mean is more uniformly scattered, and reward advantage achieves a better balance, providing a broader yet also focused sampling range.
- Figure 9: The *weak correlation* between reward variance and reward advantage shows that variance *cannot* serve as a substitute for advantage as a proxy for informativeness.

We have discussed the contrastive curriculum hypothesis in § 3.4 to support using reward advantage in the sense that the induced samples tend to decrease the loss the most in the contrastive optimization. Furthermore, assuming the optimization algorithm can converge to the *more optimal* responses, neither reward mean nor variance directly capture the learning potential of such responses – one may easily construct cases with identical variance yet differ much in reward range – thus variance fails to distinguish such scenarios. By contrast, reward advantage estimate inherently captures the relative improvement towards better response, and is sensitive to differences in reward range; variants of advantage estimate are commonly used in literature, and we discuss underlying principles in § H.

G. Extended Literature Review for Open-Ended Learning

The design of our game-theoretic framework for language model post-training is inspired from many prior works in open-ended learning. The central idea of open-ended learning is not to optimize for a specific, static distribution, but to develop an agent that can generalize well across unseen, novel environments, which are the environments that the agent has not been explicitly trained on. To achieve this, unsupervised environment design proposes to generate environments that present a curriculum of *increasing complexity* for the agent to evolve, which ensures that the agent's learning is not *narrow*, but broad enough to handle the diversity of complexity of future environments. In such curriculum, as the agent solves simpler environments, it moves on to more difficult ones, thus progressively builds more sophisticated strategies. Furthermore, by adopting a minimax regret framework, this approach adds a layer of robustness by minimizing the agent's performance gap in worst-case (*i.e.*, most adversarial) environments. In addition to distinctions discussed in § 5, we here list several foundational works in this line, and encourage the LLM community to explore with more rigor and depth: Schmidhuber (1991) presents an initial investigation into open-ended learning via self-supervised curiosity-driven exploration; Wang et al. (2019) emphasize co-evolution of environments and agent policies by training a population of agents that adapt to and solve progressively complex challenges; Dennis et al. (2020) formally introduce the notion of Unsupervised Environment Design (UED), where a protagonist and antagonist agent pair simulates regret by competing in shared environments, driving the protagonist (the main learner) to adapt to increasingly challenging scenarios; Jiang et al. (2021b) introduce Prioritized Level Replay (PLR), which uses a rolling buffer of high-regret levels to dynamically adjust the training curriculum, and selects levels with the higher learning potential; Parker-Holder et al. (2022) further propose improvements by editing previously high-regret levels; Hughes et al. (2024b) present a formal definition for open-ended system with respect to novelty and learnability, that generalizes various systems, e.g., AlphaGo (Silver et al., 2016), AdA (Team et al., 2021), etc.

H. Extended Illustration on the Methodology

This is an extended version of § 3. In § H.1, we re-present the open-ended RLHF principle in Definition 1, and discuss the intuition under the KL regularization. In § H.2, we show heuristic approaches in open-ended learning to approximate this objective, with a focus on minimax game formulation. In § H.3, we formalize the regret objective in our RLHF setting, and discuss the regret minimization for the solver and the regret maximization for the creator.

H.1. The Conceptual Open-Ended RLHF Formulation

Classical RLHF optimizes over a static prompt set:

$$\max_{\theta} \mathbb{E}_{\mathbf{x} \sim \mathcal{D}, \mathbf{y} \sim \pi_{\theta}(\cdot | \mathbf{x})} \Big[r(\mathbf{x}, \mathbf{y}) \Big] - \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} \Big[\beta \cdot \mathbb{D}_{\mathrm{KL}} \Big[\pi_{\theta}(\mathbf{y} \mid \mathbf{x}) \parallel \pi_{\mathrm{SFT}}(\mathbf{y} \mid \mathbf{x}) \Big] \Big].$$

We propose to drop the static prompt set assumption, and jointly update the prompt distribution via a creator policy for Open-Ended RLHF, with the ideal objective below:

$$\max_{\boldsymbol{\phi},\boldsymbol{\theta}} \mathbb{E}_{\mathbf{x} \sim \pi_{\boldsymbol{\phi}}(\cdot), \mathbf{y} \sim \pi_{\boldsymbol{\theta}}(\cdot \mid \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \beta \cdot \mathbb{D}_{\mathrm{KL}} \left[\pi_{\boldsymbol{\phi}}(\mathbf{x}) \cdot \pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \parallel p_{\mathrm{ref}}(\mathbf{x}) \cdot \pi_{\mathrm{SFT}}(\mathbf{y} \mid \mathbf{x}) \right].$$

This generalizes RLHF (Eq. 1). We can rewrite Eq. 7 with modified coefficients for precision:

$$\max_{\boldsymbol{\phi},\boldsymbol{\theta}} \mathbb{E}_{\mathbf{x}\sim\pi_{\boldsymbol{\phi}}(\cdot)} \left[\underbrace{\mathbb{E}_{\mathbf{y}\sim\pi_{\boldsymbol{\theta}}(\cdot|\mathbf{x})} \left[r(\mathbf{x},\mathbf{y}) \right] - \beta_{1} \cdot \mathbb{D}_{\mathrm{KL}} \left[\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \parallel \pi_{\mathrm{SFT}}(\mathbf{y} \mid \mathbf{x}) \right]}_{\mathrm{solver}} \right] - \beta_{2} \cdot \underbrace{\mathbb{D}_{\mathrm{KL}} \left[\pi_{\boldsymbol{\phi}}(\mathbf{x}) \parallel p_{\mathrm{ref}}(\mathbf{x}) \right]}_{\mathrm{creator}}.$$

The newly proposed p_{ref} represents an *underspecified*, potentially intractable probability distribution over possible tasks in the **open-ended world** (instatiated *via* prompts) – it is *not* the initial static training prompt distribution (which is only the seed set for the creator to evolve upon); it can be seen serve as a conceptual guide to steer the prompt distribution.

To further clarify, there are two types of regularization in open-ended RLHF:

- $\mathbb{D}_{\text{KL}} [\pi_{\theta}(\mathbf{y} \mid \mathbf{x}) \parallel \pi_{\text{SFT}}(\mathbf{y} \mid \mathbf{x})]$: this is the classical regularization on the response policy, ensuring that no matter how the training distribution over prompts evolves during optimization, the response policy remained anchored to the supervised fine-tuned (SFT) policy.
 - This KL (and preference optimization) is explicitly achieved in plug-in algorithms (*e.g.*, DPO) in Algo. 1. We later show how it relates to solver's regret minimization.
- $\mathbb{D}_{\mathrm{KL}}\left[\pi_{\phi}(\mathbf{x}) \parallel p_{\mathrm{ref}}(\mathbf{x})\right]$: this probability matching term captures the intuition on optimizing $\pi_{\phi}(\mathbf{x})$ to approach the conceptualized $p_{\mathrm{ref}}(\mathbf{x})$, in the sense that a language model optimizes itself by adapting its training distributions with newly generated prompts for self-training to develop increasingly general capabilities, directing its learning towards informative, new tasks (Jiang, 2023), instead being constrained in a static, pre-defined set of tasks.
 - This conceptual KL is **implicitly achieved** by the creator step in the current **eva** setting by training on a *sequence of informative prompt sets*. We later show how it relates to **creator's regret maximization**. As illustrated in § 3.3.1, we start from the seed prompt set, choose those high-regret prompts and generate variations upon them by EvolInstruct, then mixing with a buffer of the original set to form the new training distribution at each iteration. This approach resembles classical open-ended learning in § H.2, and we hope it can serve as a small step for future works to build upon.
 - A common misunderstanding among readers may be to confuse the open-ended reference $p_{ref}(\mathbf{x})$ with the initial seed prompt distribution \mathcal{D} , which is static. In contrast, $p_{ref}(\mathbf{x})$ represents a broader space of tasks (*e.g.*, user prompts in the real wild world), as a conceptual target derived from the *underspecified distribution* (Dennis et al., 2020), *i.e.*, an environment with free parameters that control. Let's use an illustrative example with Fig. 6: the prompt distribution may be defined along several dimensions (*e.g.*, the number or complexity of coding problems); a potential creator can be designed to modify these dimensions, steering the initial \mathcal{D} to new training distributions, by certain decision rules (*e.g.*, minimax regret, which offers worst-case guarantees) that forms *a sequence of informative prompts* for training.

This joint optimization objective only serves as a general principle. In the next, we discuss how existing works **implicitly achieve** the open-ended learning objective through **two-player games**.

H.2. Approaching Open-Ended Learning by Unsupervised Environment Design

H.2.1. The Asymmetric Game Formulation for Unsupervised Environment Design

While we cannot directly train the agent with the intractable $p_{ref}(\mathbf{x})$ of the open-ended world, it is possible to curate a **curriculum of prompt distributions** to improve over the static distribution and support the *continual training* of the policy $\pi_{\theta}(\cdot|\mathbf{x})$, for it to keep improving and succeed over the full task space, thus conceptually approaching $p_{ref}(\mathbf{x})$. This is often framed as an **asymmetric two-player game**.

Dennis et al. (2020) first formally define this problem as Unsupervised Environment Design (UED). The idea is that while the real-world environments are inexhaustible and hard to tract, there may exist some free parameters (*e.g.*, height and roughness in a maze) which one may control to generate new environments; UED then concerns about designing a distribution of those free parameters (*i.e.*, settings) to create new fully specified environments, that can be used to train the agents.

In this setup, one player, the **creator**, generates new environments based on some specific decision rules (see the following), while the other player, the **solver**, optimizes its policy within these training environments, and the process continues iteratively. Common **heuristic strategies** include:

- **Randomization**: environments are generated uniformly and independently of the solver's current policy. This method is simple but less effective (Tobin et al., 2017).
- **Maximin**: the creator generates environments that minimize the solver's maximum possible reward, which can often lead to unsolvable scenarios (Khirodkar and Kitani, 2018).
- **Minimax regret**: The creator targets environments that maximize the solver's *regret*, defined as the difference between the optimal return achievable and that of the solver's current policy (Beukman et al., 2024b). The regret is often conceived as the **creator's utility**.

Among them⁴, the minimax regret approach presents a sweet spot where the creator can create hard yet solvable environments, and is often empirically better. The minimax regret strategy also implies that the agent's policy is trained to perform well under all levels/settings, thus enjoys a worst-case guarantee. However, while it is often straightforward for the solver to minimize the regret (*e.g.*, through direct policy optimization, as we discuss in § H.3), the optimal policy remains *unknown* during the optimization process, thus regret as the decision signal is often intractable to the creator – which requires *approximation* (this is described as the Achilles' heel of those curriculum RL methods by Parker-Holder et al. (2022)).

Note the solvers are often directly trained with PPO (Schulman et al., 2017) under the environments.

H.2.2. Approximating the Regret and Generating New Environments

In general, the **creator** design in this line of research contains two steps:

- 1. identifying high-regret levels using different (often heuristic) regret approximation;
- 2. generating new environments by making variations or retrieving from buffers on high-regret levels.

We hereby review major works on regret approximation and environment generation as follows:

Dennis et al. (2020) propose joint training for the creator and two competing solvers.

- **Regret approximation**: here, two solver policies are trained, with the regret approximated as the **difference in their returns**. During each optimization step, one solver *maximizes* this regret, the other *minimizes* it, and the creator maximizes it.
- Environment generation: the system directly sample the parameter from the creator policy and use that to specify the environment.

Jiang et al. (2021b) propose to random sampling on high-regret levels.

- **Regret approximation**: as a heuristic, the authors use *positive value loss*, which is a function of Generalized Advantage Estimate (Schulman et al., 2015) (which itself is a function of the TD error the difference between the expected and the actual returns) as the creator's utility.
- Environment generation: the creator have a rolloing buffer of highest-regret levels by random searching on relevant configurations.

⁴We have implemented variants of these in § 4.2.1, and show minimax regret is empirically better.

Jiang et al. (2021a) further propose a double-creator setting based on (Jiang et al., 2021b), where one creator is actively generating new environments, and the other is retrieving from the buffer.

Parker-Holder et al. (2022) propose to sample high-regret levels and generate new environments by making *edits* on existing ones. The regret approximation is the same as (Jiang et al., 2021b) – the positive value loss. For environment generation, the authors suggest a general editing/mutation mechanism, where the creator chooses from high-regret levels and make small variations within an edit distance. There is an additional filtering step: they do not directly train on newly generated levels, but evaluate on those levels first, then add only the high-regret ones to the training buffer.

H.3. Regret Formulation for Open-Ended RLHF

Next, we discuss the regret minimization and maximization in our setting for alignment. Specifically:

- **Regret minimization for the solver**: we avoid calculating regret and use direct policy optimization (*e.g.*, DPO) to equivalently achieve regret minimization.
- **Regret maximization for the creator**: similarly to (Jiang et al., 2021b; Parker-Holder et al., 2022), we first find an approximation of regret, then curate new environments for the solver to train on by (i) sampling from a replay buffer of existing prompts, and (ii) making variations (through EvolInstruct (Xu et al., 2023a)) on those high-regret prompts. Specifically, we use **advantage-based estimates of the current policy**, as summarized in Table 2.

This asymmetric game serves as one potential modeling choice to implicitly achieve the open-ended RLHF principle that we proposed in Definition 1. We look forward to exploring more principled solutions in future.

Preliminaries. Let $r(\cdot, \cdot)$ be an oracle reward model. The (unregularized) optimal policy is:

$$\pi^{\star} = \arg \max_{\pi} \mathbb{E}_{\mathbf{x} \sim \mathcal{D}, \mathbf{y} \sim \pi(\cdot | \mathbf{x})} \Big[r(\mathbf{x}, \mathbf{y}) \Big].$$

We have the optimal advantage / the negated regret as:

$$A^{\star}(\mathbf{x}, \mathbf{y}) = r(\mathbf{x}, \mathbf{y}) - \mathbb{E}_{\mathbf{y}' \sim \pi^{\star}(\cdot | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}') \right]$$
$$= r(\mathbf{x}, \mathbf{y}) - V^{\star}(\mathbf{x}, \mathbf{y}).$$

Classical preference-based RL assumes a *reward*-based preference model, that is:

$$P\left(\mathbf{y}^{+} \geq \mathbf{y}^{-}\right) = \frac{\exp\left(r\left(\mathbf{x}, \mathbf{y}^{+}\right)\right)}{\exp\left(r\left(\mathbf{x}, \mathbf{y}^{+}\right)\right) + \exp\left(r\left(\mathbf{x}, \mathbf{y}^{-}\right)\right)}.$$

As a side note (Hejna et al., 2023), this is equivalent to the *advantage/regret*-based preference model, due to the bandit setup in RLHF:

$$P\left(\mathbf{y}^{+} \geq \mathbf{y}^{-}\right) = \frac{\exp\left(r\left(\mathbf{x}, \mathbf{y}^{+}\right) - V^{\star}(\mathbf{x}, \mathbf{y})\right)}{\exp\left(r\left(\mathbf{x}, \mathbf{y}^{+}\right) - V^{\star}(\mathbf{x}, \mathbf{y})\right) + \exp\left(r\left(\mathbf{x}, \mathbf{y}^{-}\right) - V^{\star}(\mathbf{x}, \mathbf{y})\right)}$$
$$= \frac{\exp\left(A^{\star}\left(\mathbf{x}, \mathbf{y}^{+}\right)\right)}{\exp\left(A^{\star}\left(\mathbf{x}, \mathbf{y}^{+}\right)\right) + \exp\left(A^{\star}\left(\mathbf{x}, \mathbf{y}^{-}\right)\right)}.$$

In our current setting, we assume there is an oracle preference model for the preference pair labeling.

KL-regularized regret. In the RLHF setting at fixed prompt distribution, the objective is:

$$\max_{\pi_{\theta}} \mathbb{E}_{\mathbf{x} \sim \pi_{\phi}(\cdot), \mathbf{y} \sim \pi_{\theta}(\cdot | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} \left[\beta \cdot \pi_{\phi}(\cdot)_{\mathrm{KL}} \left[\pi_{\theta}(\mathbf{y} | \mathbf{x}) \parallel \pi_{\mathrm{SFT}}(\mathbf{y} | \mathbf{x}) \right] \right]$$

The optimal policy of the above KL-constrained objective is:

$$\pi_{\mathrm{KL}}^{\star}(\mathbf{y} \mid \mathbf{x}) = \frac{1}{Z(\mathbf{x})} \pi_{\mathrm{SFT}}(\mathbf{y} \mid \mathbf{x}) \exp\left(\frac{1}{\beta} \cdot r(\mathbf{x}, \mathbf{y})\right),$$

where the partition function is defined as $Z(\mathbf{x}) = \sum_{\mathbf{y}} \pi_{ref}(\mathbf{y} \mid \mathbf{x}) \exp\left(\frac{1}{\beta}r(\mathbf{x}, \mathbf{y})\right)$.

We can now formally define the *regret* with regard to $\pi_{KL}^{\star}(\cdot \mid \mathbf{x})$ as:

$$\operatorname{Regret}_{\operatorname{KL}}(\mathbf{x}, \pi_{\theta}) = \mathbb{E}_{\mathbf{y} \sim \pi_{\theta}(\cdot | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \mathbb{E}_{\mathbf{y} \sim \pi_{\operatorname{KL}}^{\star}(\cdot | \mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right].$$
(14)

Regret Minimization for the Solver. It is rather straightforward/trivial to understand the objective of the solver $\pi_{\theta}(\cdot | \mathbf{x})$ as regret minimization, since the goal is to align the policy $\pi_{\theta}(\cdot | \mathbf{x})$ with the KL-optimal solution $\pi_{\text{KL}}^{\star}(\cdot | \mathbf{x})$, which directly minimizes the KL-regularized regret by design. This formulation allows flexibility in the plug-in preference optimization algorithms for the solver's step in Algorithm 1, and ensures *the alignment problem is well-defined*. In practice, we use Direct Preference Optimization (DPO) and its variants, which approximate the KL-optimal solution by iteratively adjusting π_{θ} to reflect preference differences.

Regret Maximization for the Creator. As discussed previously, while it is often trivial for the solver to minimize the regret through direct policy optimization, the optimal policy remains unknown during the optimization process, thus we cannot directly calculate the regret – we must approximate it when using it as the utility for the creator. Similarly to heuristics proposed by prior works (Jiang et al., 2021a,b; Parker-Holder et al., 2022), we use the advantage-based estimate:

$$\operatorname{Regret}(\mathbf{x}, \pi_{\theta}) | \leftarrow \operatorname{info}_{\theta}(\mathbf{x}) := r(\mathbf{x}, \mathbf{y}_{+}) - r(\mathbf{x}, \mathbf{y}_{\text{baseline}}),$$
(15)

where

$$\mathbf{y}_{+} := \arg \max_{\mathbf{y}_{i}} r(\mathbf{x}, \mathbf{y}), \tag{16}$$

$$\mathbf{y}_{\text{baseline}} := \arg\min_{\mathbf{v}_i} r(\mathbf{x}, \mathbf{y}) \text{ or } \mathbf{y}_{\text{baseline}} := \arg_{\mathbf{v}_i} r(\mathbf{x}, \mathbf{y}), \tag{17}$$

and $\{\mathbf{y}_i\}_{i=1}$ is a set of responses sampled from $\pi_{\theta}(\cdot | \mathbf{x})$ and $r(\cdot, \cdot)$ is the reward oracle. We use $\arg \min_{\mathbf{y}_i} r(\mathbf{x}, \mathbf{y})$ by default due to its simplicity and efficiency (see also § 3.4 for additional interpretation) and consistent strong empirical gains we observed in vast experiments. As the policy optimizes, the proxy should approximate the true regret better. We leave exploration of other informativeness proxy designs in **eva** to future work.

For new environment generation, as illustrated in § 3.3.1, we start from the seed prompt set, choose those high-regret prompts and generate variations upon them, then mixing with a buffer of the original set to form the new training distribution at each iteration.



I. Examples on Prompts and Model Generations

Figure 10 | The initial prompt distribution of AlpacaEval by <code>bart-large-mnli</code> with 0-shot classification, which is imbalanced. For the reward distribution, the category with lowest average reward has the highest reward gap (*i.e.*, the default informativeness proxy), implying the potential to improve.

initial prompt \rightarrow	Write me the code for a distributed transaction manager.\nThink
	step by step and use pseudo code first.\nThen, define interfaces
	for all involved actors and entitles. (nuse Rational Unified
	approach for this part. In honry then move on to the actual
	implementation, class-by-class, and method-by-method. And we the
	code be implemented in C# and forlow Solid principles.
evolved #1 \rightarrow	Craft a suite of syntax for a distributed transaction coordinator.
	Start with a sequential breakdown in pseudocode format. Following
	that, establish the protocols for communication and interaction
	amongst the various participants and components, incorporating
	the Rational Unified Process methodology.\n\nProceed thereafter to
	the concrete creation, detailing each class and function. Ensure
	that the final C# code adheres to the precepts of SULID and is
orrolared #2	Device a comprehensive set of directives and structures for a
evorveu #2	distributed transaction coordinator architecture. Initiate by
	formulating a step-by-step algorithmic decomposition in pseudocode
	Subsequently, delineate the frameworks for dialog and cooperation
	between the numerous entities and elements, utilizing the tenets
	of the Rational Unified Process methodology.\n\nContinue to the
	actual generation of the code, meticulously detailing every class
	and corresponding method. Guarantee that the culminating C# code
	is in strict compliance with SOLID principles and is supplemented
	with descriptive commentary to enhance future clarity and upkeep,
	while also validating the code against a set of unit tests to
	ensure robust functionality.
evolved #3 \rightarrow	Commence by constructing an algorithm in pseudocode that
	meticulously breaks down the sequential stages for a distributed
	transaction coordinator system. Progress by outlining the
	communication protocols and collaborative mechanisms among the
	myriad components, adhering to the Rational Unified Process
	approach. \n \nAdvance to craiting the code in C#, ensuring each
	design principles. Integrate thereugh comments for heightened
	maintainability and conduct comprehensive unit testing for assured
	operational integrity
evolved #4 →	Design a detailed flowchart that represents the intricate
	steps of an orchestration engine for managing microservices
	in a cloud-native environment. Begin by detailing the service
	discovery, load balancing, and fault tolerance strategies, while
	incorporating the DevOps philosophy.\n\nProceed by developing the
	implementation in Java, focusing on clean, modular code following
	object-oriented programming best practices. Accompany your
	code with clear documentation for easy understanding and perform
	rigorous integration testing to guarantee robustness.

Table 16 | Examples of evolved prompts from AlpacaEval. We suggest practitioners to include generated responses with oracle rewards and self-critique in the context for better prompt evolving, which is helpful for mitigating the effect of potential self-consuming loops in synthetic data training.

1st-turn prompt: When a number is div remainder when twice the number is divided by	ided by 10, the remainder is 4. What is the by 4?
Answer from gemma-2-9b-it-dpo	Answer from gemma-2-9b-it-dpo-eva
<pre>Here's how to solve this problem: 1. Understand the first statement: * "When a number is divided by 10, the remainder is 4" means the number can be represented as 10*k + 4, where k is an integer. 2. Double the number:</pre>	Here's how to solve this problem: 1. Understand the first statement: - "When a number is divided by 10, the remainder is 4" means the number can be represented as 10*k + 4, where k is an integer.
<pre>* Twice the number is 2*(10*k + 4) = 20*k + 8 3. Divide by 4: * (20*k + 8) divided by 4 is (20*k)/4 + 8/4 = 5*k + 2 4. Find the remainder: * Since 5*k is a multiple of 4, the remainder when twice the number is divided by 4 is 2. Let me know if you'd like to try another example! 2nd-turn prompt: What about when twice the n</pre>	 Double the number: Twice the number is 2*(10*k + 4) = 20*k + 8 3. Divide by 4: When (20*k + 8) is divided by 4, the 20*k term is perfectly divisible by 4. The remainder will be the same as the remainder when 8 is divided by 4, which is 0. Therefore, the remainder when twice the number is divided by 4 is 0.
Answor from comma-2-9b-it-doo	Answor from comma-2-9b-it-dpo-owa
Here's how to solve that: 1. We know: Twice the number is 20*k + 8 (from the previous calculation). 2. Divide by 5: (20*k + 8) divided by 5 is (20*k)/5 + 8/5 = 4*k + 1.6 3. Find the remainder: Since 4*k is a multiple of 5, the remainder when twice the number is divided by 5 is 1. Let me know if you have any more number theory puzzles!	<pre>Here's how to solve that: 1. Twice the number: We know twice the number is 20*k + 8 (from the previous steps). 2. Divide by 5: * 20*k is divisible by 5. * 8 divided by 5 leaves a remainder of 3. Therefore, the remainder when twice the number is divided by 5 is 3.</pre>
Judgment (by gpt-4)	
Tedement for some 2 Ob it day	Tudement for come 2 0h it das sus
The assistant's response is incorrect. The assistant incorrectly calculated the remainder when twice the number is divided by 5. The assistant calculated the decimal part of the division operation, not the remainder. The correct calculation should be $(20n + 8) \ \% \ 5 = (20n \ \% \ 5) + (8 \ \% \ 5) = 0 + 3 = 3$. Therefore, the remainder when twice the number is divided by 5 is 3, not 1 as the assistant stated.	The assistant's answer is correct and matches the reference answer. The assistant correctly explains that twice the number is 20*k + 8 and that when this is divided by 5, the remainder is 3. The assistant's explanation is clear and easy
<pre>The corrected response would be: 1. We know: Twice the number is 20*k + 8 (from the previous calculation). 2. Divide by 5: (20*k + 8) divided by 5 gives us a remainder of (20*k % 5) + (8 % 5) = 0 + 3 = 3. 3. Find the remainder: The remainder when twice the number is divided by 5 is 3. Rating: [[3]], "score": 3, "turn": 2, </pre>	<pre>to understand, making it helpful for the user. There are no mistakes to correct. Rating: [[10]], "score": 10, "turn": 2, "tstamp": 1722846518.5543818</pre>
"tstamp": 1722737011.7768948	

Table 17 | Comparison of model generations on examples from MT-Bench.

1st-turn prompt: Imagine you are writing a blog post comparing two popular smartphone models. Develop an outline for the blog post, including key points and subheadings to effectively compare and contrast the features, performance, and user experience of the two models. Please answer in fewer than 200 words

Answer from gemma-2-9b-it-dpo

Smartphone Showdown: [Model A] vs. [Model B]\n\n**I. Introduction**\n* Briefly introduce the two smartphone models being compared, highlighting their popularity and target audience.\n* State the purpose of the comparison: to help readers decide which phone best suits their needs. \n \n**II. Design and Display** \n* Physical dimensions, weight, and build quality comparison.\n* Screen size, resolution, and display technology (e.g., OLED, LCD).\n* Design aesthetics and user preferences.\n\n**III. Performance and Specs**\n* Processor, RAM, and storage comparison.\n* Benchmark scores and real-world performance analysis.\n* Battery life and charging capabilities.\n\n**IV. Camera Capabilities**\n* Rear and front camera specs (megapixels, aperture, features). \n* Image quality comparison in various lighting conditions.\n* Video recording capabilities.\n\n**V. Software and User Experience ** \n* Operating system and user interface mparison.\n* App ecosystem and availability.\n* Software features and customization options. $\n**VI$. Price and Value**\n* Compare the price points of both models.\n* Analyze the value proposition based on features and performance.\n\n**VII. Conclusion**\n* Summarize the key differences and similarities.\n* Recommend the best phone for specific user profiles (e.g., budget-conscious, photography enthusiasts, gamers).

Answer from gemma-2-9b-it-dpo-eva

iPhone 14 Pro vs. Samsung Galaxy S23: Which Flagship Reigns Supreme?\n\n**I. Introduction**\n* Briefly introduce both smartphones and their position in the market. \n* State the purpose of the comparison: to help readers decide which phone best suits their needs.\n\n**II. Design and Display**\n* Physical dimensions, weight, and build quality comparison.\n* Screen size, resolution, refresh rate, and display technology (OLED vs. Super AMOLED).\n* Design aesthetics and unique features (e.g., notch vs. punch-hole, color options).\n\n**III. Performance and Camera**\n* Processor comparison (Apple A16 Bionic vs. Snapdragon 8 Gen 2).\n* RAM and storage options.\n* Camera specs: megapixels, lens types, aperture, and special features (e.g., telephoto, macro).\n* Image quality comparison based on sample photos and user reviews.\n\n**IV. Software and User Experience**\n* Operating systems: iOS 16 vs. Android 13.\n* User interface comparison: intuitiveness, customization options, and app ecosystems. $\n*$ Special features: Face ID vs. in-display fingerprint sensor, voice assistants.\n\n**V. Battery Life and Charging**\n* Battery capacity and real-world usage comparison.\n* Fast charging speeds and wireless charging capabilities.\n\n**VI. Price and Value**\n* Compare starting prices and different storage configurations.\n* Assess the overall value for money based on features and performance.\n\n**VII. Conclusion**\n* Summarize the key differences and strengths of each phone.\n* Recommend the best phone for specific user types (e.g., photography enthusiasts, gamers, budget-conscious consumers).

2nd-turn prompt: Take your previous response and rephrase it as a limerick. Answer from gemma-2-9b-it-dpo-eva

Answer from gemma-2-9b-it-dpo

Two phones, a showdown so grand, \n[Model A] and [Model B], hand in hand.\nDesign, specs, and price,\nWe'll analyze nice,\nTo help you choose, understand?\n\nLet me know if you'd like me to try filling in the bracketed parts with specific model names!

Judgment (by gpt-4)

Judgment for gemma-2-9b-it-dpo

The assistant's response is creative and relevant to the user's request. The user asked the assistant to rephrase the previous response, which was a detailed outline for a blog post, into a limerick. The assistant successfully did so, maintaining the essence of the original response in a limerick format. The assistant also offered to further customize the limerick by filling in the bracketed parts with specific model names, showing a willingness to provide additional detail if needed. However, the limerick does not fully capture the depth and detail of the original response, which is understandable given the constraints of the limerick format.

Rating: [[8]], "score": 8, "turn": 2, "tstamp": 1722737024.0327556

\nTwo phones, a Pro and a Galaxy, \nFor flagships, they truly are spacy.\nWith cameras and screens,\nAnd processors keen, \nWhich one wins? Read on, and be savvy! \nLet me know if you'd like another limerick!

Judgment for gemma-2-9b-it-dpo-eva

The assistant's response is creative and relevant to the user's request. The assistant successfully rephrased the previous response, which was a detailed outline for a blog post comparing two smartphone models, into a limerick. The limerick is playful and engaging, and it maintains the essence of the original response, which is to compare the two phones and help the reader make $% \left({{{\boldsymbol{x}}_{i}}} \right)$ an informed decision. The assistant also offers to create another limerick if the user wants, showing a willingness to continue the interaction.

Rating: [[9]], "score": 9, "turn": 2, "tstamp": 1722846542.9437995

Table 18 | (Continued) comparison of model generations on examples from MT-Bench.

1st-turn prompt: Each problem consists of three statements. Based on the first two statements, the third statement may be true, false, or uncertain.\nl. Oranges cost more than apples.\n2. Oranges cost less than bananas.\n3. Bananas cost more than apples and bananas cost more than orange.\nIf the first two statements are true, then the third statement is?

Answer from gemma-2-9b-it-dpo	Answer from gemma-2-9b-it-dpo-eva
Here's how to break down the logic:\n\n* **Statement	Here's how to break down the logic: \n\n* **Statement
1:** Oranges > Apples (Oranges cost more than apples) $\n*$	1:** Oranges > Apples (Oranges cost more than apples)\n
Statement 2: Oranges < Bananas (Oranges cost less	**Statement 2:** Oranges < Bananas (Oranges cost less
than bananas)\n\nThis means the price order is: Bananas	than bananas) $\ \$ these statements tell us that bananas
> Oranges > Apples\n\n* **Statement 3:** Bananas	are the most expensive, then oranges, and apples are th
> Apples AND Bananas > Oranges\n\nStatement 3 is	<pre>least expensive.\n\n* **Statement 3:** Bananas > Apples</pre>
partially true.\n\n* The part "Bananas > Apples"	AND Bananas > Oranges\n\nSince bananas are indeed more
is true based on our price order.\n* The part "Bananas > $\fill \label{eq:based}$	expensive than both apples and oranges, statement 3 is
Oranges" is also true based on our price order.\n\n\nLet	**true**. \n \nLet me know if you'd like to try another
me know if you'd like to try another one!	one!

2nd-turn prompt: If the third statement is true. Is the first statement true, false, or uncertain? Please explain.

Answer from gemma-2-9b-it-dpo

If the third statement is true, the first statement is **false**.\n\nHere's why:\n\n* **Statement 3:** States that bananas cost more than both apples AND oranges.\n\nThis means the price order is: Bananas > Oranges > Apples.\n\n* **Statement 1:** States that oranges cost more than apples.\n\nIf bananas are the most expensive, and oranges are second, then oranges cannot be more expensive than apples.\n\nlnLt me know if you have any other logic puzzles!

Answer from gemma-2-9b-it-dpo-eva

If the third statement is true, then the first statement is **uncertain**.\n\nHere's why:\n\n* **Statement 3:** Bananas > Apples AND Bananas > Oranges\n\nThis tells us bananas are the most expensive, but it doesn't explicitly state the relative prices of apples and oranges.\n\n* **Statement 1:** Oranges > Apples\n\nThis statement claims oranges are more expensive than apples.\n\nStatement 3 doesn't contradict statement 1, but it also doesn't confirm it. It's possible that oranges *are* more expensive than apples, but statement 3 alone doesn't give us enough information to be sure.

Judgment (by gpt-4)

Judgment for gemma-2-9b-it-dpo

The assistant's response is incorrect. The assistant states that if the third statement is true, the first statement is false. However, the third statement only establishes that bananas cost more than both apples and oranges. It does not provide information about the relative costs of apples and oranges. Therefore, the first statement could be true (if oranges cost more than apples), false (if oranges cost less than apples), or uncertain (if oranges and apples cost the same). The assistant's explanation is flawed because it incorrectly assumes that the order of costs must be Bananas > Oranges > Apples, when in fact the order could also be Bananas > Apples = Oranges or Bananas > Apples > Oranges. \n\nCorrected Assistant's Answer: If the third statement is true, then bananas cost more than apples and bananas cost more than oranges. This means that oranges could still cost more than apples, making the first statement true. However, it's also possible that oranges and apples have the same cost, which would make the first statement false. Therefore, based on the third statement alone, the first statement is uncertain.

Rating: [[2]], "score": 2, "turn": 2, "tstamp": 1722737017.2808955

Judgment for gemma-2-9b-it-dpo-eva

The assistant's response is correct and helpful. The assistant explains that the first statement is uncertain if the third statement is true, which aligns with the reference answer. The assistant provides a clear explanation of why this is the case, stating that the third statement doesn't contradict the first statement, but it also doesn't confirm it. Therefore, the assistant's response is accurate and informative.\n\nThe assistant's response: "If the third statement is true, then the first statement is **uncertain**. Here's why: Statement 3: Bananas > Apples AND Bananas > Oranges. This tells us bananas are the most expensive, but it doesn't explicitly state the relative prices of apples and oranges. Statement 1: Oranges > Apples. This statement claims oranges are more expensive than apples. Statement 3 doesn't contradict statement 1, but it also doesn't confirm it. It's possible that oranges *are* more expensive than apples, but statement 3 alone doesn't give us enough information to be sure.

Rating: [[10]], "score": 10, "turn": 2, "tstamp": 1722846527.2339694

Table 19 | (Continued) comparison of model generations on examples from MT-Bench.

Answer from gemma-2-9b-it-dpo-eva

1st-turn prompt: Implement a function to find the median of two sorted arrays of different sizes with O(1) space complexity and O(n) time complexity

Answer from gemma-2-9b-it-dpo

Judgment (by gpt-4)

reference answer.

Judgment for gemma-2-9b-it-dpd

ets the same complexity requirements.

python\n\def find_median_sorted_arrays(nums1, nums2):\n """\n Finds the median of two sorted arrays of different sizes.\n\n Args:\n nums1: The first sorted array. \n nums2: The second sorted array. \n \n Returns: \n The median of the two sorted arrays. \n """\n\n m, n = len(nums1), len(nums2) \n if m > n:\n nums1, nums2, m, n = nums2, nums1, n, m # Ensure m <= n\n\n imin, imax, half_len = 0, m, (m + n + 1) // $2\lnn$ while imin <= imax:\n i = (imin + imax) // 2\n j = half_len - i\n if i < m and nums2[j - 1] > nums1[i]:\n imin = i + 1 # i is too small, increase it\n elif i > 0 and nums1[i - 1] > nums2[j]:\n imax = i - 1 # i is too big, decrease it\n else:\n # i is perfect\n\n if i -- 0:\n max_left = nums2[j - 1]\n elif j -= 0:\n max_left = nums1[i - 1]\n else:\n max_left = max(nums1[i -1], nums2[j - 1])\n\n if (m + n) % 2 -- 1:\n return max_left\n\n if i -- m:\n min_right = nums2[j]\n elif j -- n:\n min_right = nums1[i]\n else:\n min_right = min(nums1[i], nums2[j])\n\n return (max_left + min_right) / 2.0\n\n# Example usage\nnums1 = [1, 3]\nnums2 = [2]\nmedian - find_median_sorted_arrays(nums1, nums2)\nprint(f"The median of {nums1} and {nums2} is: {median}")\n\n\n**Explanation:**\n\n1. **Handle Unequal Lengths:** \n - If `nums1` is longer than `nums2`, swap them to ensure `nums1` is always the shorter array. This simplifies the logic.\n\n2. **Binary Search:**\n - The core idea is to use binary search on the shorter array ('nums1').\n - 'imin' and 'imax' define the search range for the partition point 'i' in 'nums1'.\n - 'half_len' calculates the desired total number of elements on the left side of the partition (to find the median).\n\n3. **Partitioning:**\n - In each iteration, 'i' divides 'nums1' into two parts: 'nums1[0:i] ' and 'nums1[i:m] '.\n - 'j' is calculated to divide 'nums2' so that the total number of elements on the left side is 'half_len'.\n\n4. **Adjusting the Partition:**\n - We compare elements at the boundaries of the partitions to see if 'i' is in the correct position:\n - If 'nums2[j - 1] > nums1[i]', 'i' is too small, so we move 'imin' to 'i + 1'.\n - If 'nums1[i - 11 > nums2[1]', 'i' is too large, so we move 'imax' to 'i - 1'.\n\n5. **Finding the Median:**\n - Once 'i' is in the correct position, we find:\n - 'max_left': The maximum element in the left partitions of both arrays.\n 'min right': The minimum element in the right partitions of both arrays.\n If the total length is odd, 'max_left' is the median.\n - If the total length is even, the median is the average of <code>`max_left'</code> and <code>`min_right`.\n\n**Time</code> Complexity:** O(log(min(m, n))) because we perform binary search on the shorter array.\n\n**Space Complexity:** O(1) as we only use a constant am of extra space for variables.

-- m:\n min_right - nums2[j]\n elif j -- n:\n min_right - nums1[i]\n
else:\n min_right - min(nums1[i], nums2[j])\n\n return (max_left +
min_right) / 2.0\n\n# Example usage\nnums1 - [1, 3]\nnums2 - [2]\nmedian
- find_median_sorted_arrays(nums1, nums2)\nprint(f*The median of (nums1)
and (nums2) is: (median)*)\n\n\n+=Explantion:+=\n\n1. +=Handle Unequal
Lengths:+<\n - If 'nums1' is longer than 'nums2', swap them to ensure 'nums1'
is always the shorter array. This simplifies the logic.\n\n2. +=Binary
Search:+<\n - The core idea is to use binary search on the shorter array
('nums1').\n - 'min' and 'imax' define the search range for the partition
point 'i' in 'nums1'.\n - 'half_len' calculates the desired total number
of elements on the left side of the partition (to find the median).\n\n3.
+=Partitioning:+<\n - In each iteration, 'i' divides 'nums1', and 'j'
divides 'nums2' such that the total number of elements on the left side is</pre>

python\n\def find_median_sorted_arrays(nums1, nums2):\n """\n Finds the

median of two sorted arrays of different sizes.\n\n Args:\n nums1: The

if m > n:\n nums1, nums2, m, n = nums2, nums1, n, m # Ensure m <= n\n\n

imin, imax, half_len = 0, m, $(m + n + 1) // 2 \ln n$ while imin <= imax:\n

i = (imin + imax) // 2\n j = half_len - i\n if i < m and nums2[j - 1]

> nums1[i]:\n imin = i + 1 # i is too small, increase it\n elif i > 0

and numsl[i - 1] > nums2[i]:\n imax = i - 1 # i is too big, decrease it\n

else:\n # i is perfect\n\n if i -- 0:\n max_left - nums2[j - 1]\n elif

j -- 0:\n max_left - nums1[i - 1]\n else:\n max_left - max(nums1[i -

1], nums2[j - 1])\n\n if (m + n) % 2 -- 1:\n return max_left\n\n if i

first sorted array.\n nums2: The second sorted array.\n\n Returns:\n The

median of the two sorted arrays. \n """\n\n m, n = len(nums1), len(nums2) \n

'half_len'.\n\n4. **Adjusting the Search Range:**hn - If 'nums2[j - 1] > nums1[j', it means 'i' is too small, so we need to move the partition point in 'nums1' to the right ('imin = i + 1').\n - If 'nums1[i - 1] > nums2[j]', 'i' is too large, so we move it to the left ('imax - i - 1').\n\n5. **Finding the Median:**\n - When the correct partition is found ('i' is in the right position), we find:\n - 'max_left': The maximum element on the left side of the partition.\n - 'min_right': The minimum element on the right side of the partition.\n - If the total number of elements is odd, 'max_left' is the median.\n - If even, the median is the average of 'max_left' and 'min_right'.\n\n*Time Complexity:** O(log(min(m, n))) because we are performing binary search on the shorter array.\n\n**Space Complexity:** O(1) as we are only using a constant amount of extra space for variables.

Judgment for gemma-2-9b-it-dpo-eva

The assistant's answer is correct and provides a detailed explanation of the code. The assistant correctly states that the time complexity is O(log(min(m, n))) and the space complexity is O(l), which aligns with the reference answer. The assistant also provides a step-by-step explanation of the code, which is very helpful for understanding the logic behind the solution. The assistant's code is also correct and will correctly find the median of two sorted arrays of different sizes. Therefore, there are no corrections needed for the assistant's response.

Rating: [[10]], "score": 10, "turn": 1, "tstamp": 1722846533.772981

Rating: [[8]], "score": 8, "turn": 1, "tstamp": 1722737514.2011044

The assistant's answer is correct and provides a detailed explanation of the code. The assistant correctly states that the time complexity is $O(\log(\min(m, n)))$ and the space complexity is O(1), which aligns with the reference answer.

helpful for understanding how to use it. The assistant's code is a different

implementation than the reference answer, but it achieves the same result and

However, the assistant's answer does not address the user's original question

about achieving O(n) time complexity. The assistant should have clarified

that it's not possible to find the median of two sorted arrays of different

sizes with O(1) space complexity and O(n) time complexity, as stated in the

The assistant also provides an example usage of the function, which is

Table 20 | (Continued) comparison of model generations on examples from MT-Bench.

1st-turn prompt: You are given two sorted lists of size m and n. Implement a function to find the kth smallest element in the union of the two lists with linear complexity.

Answer from gemma-2-9b-it-dpo

"'python\n\def find kth smallest(list1, list2, k):\n """\n Finds the kth smallest element in the union of two sorted lists.\n\n Args:\n list1: The first sorted list.\n list2: The second sorted list.\n k: The desired kth smallest element.\n\n Returns:\n The kth smallest element in the union of the two i, j = 0, 0\n min_heap = [] \n\n # Build a min-heap with the first elements of both lists $\$ for x in range (min (m, n)): $\$ heapq.heappush (min heap, (list1[x], x, 0)) # (value, list_index, position_in_list)\n heapq.heappush(min_heap, (list2[x], x, 1))\n\n # Extract k smallest elements from the heap\n for _ in range(k - 1): $n _, _, _ = heapq.heappop(min_heap) n/n$ # The top element of the heap is the kth smallest \n return heapq.heappop(min_heap)[0]\n\n# Example usage:\nlist1 = [2, 5, 8, 12]\nlist2 = [1, 3, 7, 9, 10]\nk = 5\nkth_smallest = find_kth_smallest(list1, list2, k)\nprint(f"The {k}th smallest element is: {kth_smallest}")\n\n\n**Explanation:**\n\n1. **Initialization:**\n - 'm' and 'n' store the lengths of the input lists.n - 'i' and 'j' are pointers to track the current position in each list.\n - 'min heap' is a min-heap used to efficiently store and retrieve the smallest elements encountered so far.\n\n2. **Building the Min-Heap:**\n - The code iterates through the first 'min(m, n)' elements of both lists. – For each element, a tuple '(value, list_index, position_in_list)' is pushed onto the 'min_heap'. This tuple helps us keep track of the element's value, the list it belongs to, and its original position.\n\n3. **Extracting k-1 Smallest Elements:**\n - The 'for' loop runs 'k - 1' times, effectively extracting the 'k-1' smallest elements from the `min_heap`.\n\n4. **Finding the kth Smallest:**\n - After the loop, the top element of the `min_heap' contains the `k`th smallest element.\n 'heapq.heappop(min_heap) ' removes and returns this element.\n\n**Time Complexity:**\n\n- Building the min-heap: $O(m + n) \ n-$ Extracting k-1 elements: O(k + m) $\log(k)$) \n- Overall: **O(m + n + k * $\log(k)$) **, which is approximately **O(m + n) ** since 'k' is usually much smaller than `m + n`.\n\n\nLet me know if you have any other questions!

Answer from gemma-2-9b-it-dpo-eva

"'python\n\def find_kth_smallest(list1, list2, k):\n """\n Finds the kth smallest element in the union of two sorted lists.\n\n Args:\n list1: The first sorted list. \n list2: The second sorted list. \n k: The desired rank of the smallest element.\n\n Returns:\n The kth smallest element in the union of the lists.\n """\n\n i = 0 # Index for list1\n j = 0 # Index for list2\n merged = [] # Store the merged elements\n\n while i < len(list1) and j < len(list2):\n if list1[i] <= list2[j]:\n merged.append(list1[i])\n i += 1\n else:\n merged.append(list2[j])\n j += 1\n\n # Add any remaining elements from list1\n while i < len(list1):\n merged.append(list1[i])\n i += 1\n\n # Add any remaining elements from list2\n while j < len(list2):\n merged.append(list2[j])\n j += 1\n\n return merged[k - 1] # Return the kth element (index k-1)\n\n# Example usage:\nlist1 = [2, 5, 8, 12]\nlist2 = [1, 3, 7, 9, $10]\nk = 5\n\kth smallest = find kth smallest(list1,$ list2, k)\nprint(f"The {k}th smallest element is: {kth_smallest}")\n\n\n**Explanation:**\n\n1. **Initialization:**\n - 'i' and 'j' are index pointers for 'list1' and 'list2' respectively, starting at 0.\n - 'merged' is an empty list to store the merged sorted elements.\n\n2. **Merging:**\n - The 'while' loop continues as long as both 'i' and 'j' are within the bounds of their respective lists.n - In each iteration, it compares the elements at <code>`list1[i]`</code> and <code>`list2[j]`.</code> - The smaller element is appended to 'merged', and the corresponding index ('i' or 'j') is incremented.\n\n3. **Adding Remaining Elements:**\n - After one list is exhausted, the remaining elements from the other list are directly appended to `merged`.\n\n4. **Returning the kth Element:**\n - Finally, `merged[k - 1]` is returned, which represents the kth smallest element in the union (remember that list indices start from 0).\n\n**Linear Complexity:**\n\n- The algorithm iterates through each element in both lists at most once during the merging process.\n- The time complexity is therefore O(m + n), which is linear in the total number of elements (m + n), making it efficient for large lists.

Judgment (by gpt-4)

Judgment for gemma-2-9b-it-dpo

The assistant's answer is incorrect. The user asked for a solution with linear complexity, but the assistant provided a solution with a time complexity of O(m + n + k $\star \log(k)$), which is not linear. The assistant's solution uses a min-heap, which is not necessary and adds unnecessary complexity to the solution.

Rating: [[2]], "score": 2, "turn": 1, "tstamp": 1722737030.6411152

Judgment for gemma-2-9b-it-dpo-eva

The assistant's answer is correct and helpful. It provides a Python function that implements the two-pointer approach to find the kth smallest element in the union of two sorted lists. The assistant's function is slightly different from the reference, but it achieves the same goal. The assistant's function merges the two lists into a new list and then returns the kth element from the merged list. The assistant also provides a detailed explanation of how the function works and confirms that the time complexity is linear, which is what the user asked for. However, the assistant's function uses extra space to store the merged list, which is not necessary and not as efficient as the reference.

Rating: [[8]], "score": 8, "turn": 1, "tstamp": 1722846543.867601

Table 21 | (Continued) comparison of model generations on examples from MT-Bench.

		2nd-turn prompt:	Does there ex	xist an algorithm	with better time complexity?	If so, implement it.
--	--	------------------	---------------	-------------------	------------------------------	----------------------

Answer from gemma-2-9b-it-dpo

Answer from gemma-2-9b-it-dpo-eva

You are absolutely right! There's a more efficient algorithm with a time complexity of **O(m + n)** without using a heap.\n\nHere's the implementation:\n\npython\n\def find_kth_smallest_optimized(list1, list2, k):\n """\n Finds the kth smallest element in the union of two sorted lists\n with O(m + n) time complexity.\n\n Args:\n list1: The first sorted list. \n list2: The second sorted list. \n k: The desired st element.\n\n Returns:\n The kth smallest element in the union of the two lists. $\n """\n m, n = len(list1), len(list2)\n i,$ j = 0, 0\n result = []\n\n # Merge the lists while keeping track of the kth smallest\n while len(result) < k:\n if i < m and j < n:\n if list1[i] <= list2[j]:\n result.append(list1[i])\n i += 1\n else:\n i += 1\n else:\n result.append(list2[j])\n j += 1\n\n return result[k 1]\n\n# Example usage:\nlist1 = [2, 5, 8, 12]\nlist2 = [1, 3, 7, 9, 10]\nk = 5\nkth_smallest = find_kth_smallest_optimized(list1, list2, k)\nprint(f"The {k}th smallest element is: {kth_smallest}")\n\n\n**Explanation:**\n **Initialization:**\n - 'm' and 'n' store the lengths of the lists.\n - 'i' and 'j' are pointers for 'list1' and 'list2', respectively.\n - 'result' is a list to store the merged and sorted elements. \n\n2. $\star\star Merging$ and Tracking:**\n - The 'while' loop continues until 'k' elements are in the 'result' list.\n - In each iteration, it compares the current elements from 'list1' and 'list2'.\n - The smaller element is appended to 'result', and the corresponding pointer ('i' or 'j') is incremented.\n - If one list is exhausted, the remaining elements from the other list are appended to 'result'.\n\n3. **Returning the kth Smallest:**\n - Finally, 'result[k 1]' contains the 'k'th smallest element.\n\n**Time Complexity:**\n\n- The algorithm iterates through both lists once, resulting in a time complexity of **O(m + n) **.\n\n\nLet me know if you have any more questions!

we can achieve an even better solution with **O(log(min(m, n))) ** time exity using a slightly more sophisticated appro ach.\n\nThe key idea is to leverage the sorted nature of the lists and use a $\star\star {\rm binary}$ search** strategy.\n\nHere's the implementation:\n\n\##\npvthon\n\def find_kth_smallest_optimized(list1, list2, k):\n """\n Finds the kth smallest element in the union of two sorted lists with O(log(min(m, n))) time complexity.\n\n Args:\n list1: The first sorted list.\n list2: The cond sorted list. \n k: The desired rank of the smallest element. \n r Returns:\n The kth smallest element in the union of the lists.\n """\n m, n = len(list1), len(list2) n if m > n:n list1, list2, m, n = list2, list1, n, m # Ensure list1 is the shorter one\n\n left, right = 0, m\n while left <= right:\n partitionX = (left + right) // 2\n partitionY - k - partitionX\n\n maxLeftX - list1[partitionX - 1] if partitionX > 0 else float('-inf')\n minRightX = list1[partitionX] if partitionX < m else float('inf')\n\n maxLeftY = list2[partitionY - 1] if partitionY > 0 else float('-inf')\n minRightY = list2[partitionY] if partitionY < n else float('inf')\n\n if maxLeftX <= minRightY and maxLeftY <= minRightX:\n if partitionX -- 0:\n return list2[partitionY - 1]\n elif partitionY -- 0:\r return list1[partitionX - 1]\n else:\n return max(list1[partitionX - 1], list2[partitionY - 1])\n elif maxLeftX > minRightY:\n right = partitionX # Too many elements on the right side of list1\n else:\n left = partitionX + 1 # Too many elements on the right side of list2\n\n\n**Explanation:**\n\n1 **Shorten Lists:** If 'list1' is longer than 'list2', swap them to ensure 'list1' is always the shorter one. This simplifies the logic.\n\n2. **Binary Search:**\n - 'left' and 'right' pointers define the search space within 'list1'.\n - 'partitionX' is the middle point in 'list1', and 'partitionY' is calculated to divide the remaining elements in 'list2' such that 'partitionX + partitionY = k'.\n - 'maxLeftX', 'minRightX', 'maxLeftY', and 'minRightY' represent the largest element to the left and smallest element to the right of the partitions in both lists.\n\n3. **Comparison and Adjustment:**\n If the 'maxLeftX' is less than or equal to 'minRightY' and 'maxLeftY' is less than or equal to 'minRightX', it means the kth smallest element lies within the current partitions. We return the larger of 'maxLeftX' and maxLeftY'.\n - If 'maxLeftX' is greater than 'minRightY', it indicates that we need to search in the left subarray of 'list1' (i.e., decrease 'right').\n - Otherwise, we search in the right subarray of 'list1' (i.e., increase 'left').\n\n4. **Termination:** The binary search continues until 'left' crosses 'right', indicating the correct partition has been found.\n\n**Time Complexity:**\n\n- The binary search divides the search space in half at each step.n- Therefore, the time complexity is $O(\log(\min(m, n)))$, which is significantly faster than linear time for large lists where one list is much smaller than the other.

You are right to ask! While the previous algorithm has linear time complexity,

Judgment (by gpt-4)

Judgment for gemma-2-9b-it-dpo

The assistant's first response to the user's question is incorrect. The user asked for a function to find the kth smallest element in the union of two sorted lists with linear complexity. The assistant provided a function that uses a min-heap, which has a time complexity of $O(m + n + k + \log(k))$. This is not linear complexity, as the user requested. The assistant's second response to the user's question is also incorrect. The user asked if there exists an algorithm with better time complexity than linear. The assistant provided a function that has a time complexity of O(m + n), which is linear, not better than linear. The assistant should have provided a function that uses a binary search approach, which has a time complexity of $O(\log(m) +$ $\log(n))$, as the reference answer correctly does.

t Rating: [[2]], "score": 2, "turn": 2, "tstamp": 1722737031.5033472

Judgment for gemma-2-9b-it-dpo-eva

The assistant's response is correct and helpful. The assistant provided a Python function that uses a binary search approach to find the kth smallest element in the union of two sorted lists. The assistant also provided a detailed explanation of how the function works, including the time complexity of the function. The assistant's answer matches the reference answer in terms of the algorithm used and the explanation provided. The assistant also correctly identified that the binary search approach has a better time complexity than the linear approach. However, the assistant's code has a minor issue. The assistant's code does not handle the case when 'k' is greater than the sum of the lengths of the two lists. In such a case, the code will raise an 'IndexError'. This can be fixed by adding a check at the beginning of the function to return 'None' if 'k' is greater than the sum of the lengths of the two lists.

Rating: [[9]], "score": 9, "turn": 2, "tstamp": 1722846556.6828268

Table 22 | (Continued) comparison of model generations on examples from MT-Bench.

References

- Z. Abbas, R. Zhao, J. Modayil, A. White, and M. C. Machado. Loss of plasticity in continual deep reinforcement learning. In *Conference on Lifelong Learning Agents*, pages 620–636. PMLR, 2023.
- D. Abel, A. Barreto, B. Van Roy, D. Precup, H. P. van Hasselt, and S. Singh. A definition of continual reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2024.
- A. Ahmadian, C. Cremer, M. Gallé, M. Fadaee, J. Kreutzer, A. Üstün, and S. Hooker. Back to basics: Revisiting reinforce style optimization for learning from human feedback in llms. arXiv preprint arXiv:2402.14740, 2024.
- K. J. Arrow. Social choice and individual values, volume 12. Yale university press, 1952.
- J. T. Ash and R. P. Adams. On the difficulty of warm-starting neural network training. *arXiv preprint arXiv:1910.08475*, 2019.
- A. Banos. On pseudo-games. The Annals of Mathematical Statistics, 39(6):1932–1945, 1968.
- Y. Bengio, J. Louradour, R. Collobert, and J. Weston. Curriculum learning. In Proceedings of the 26th annual international conference on machine learning, pages 41–48, 2009.
- M. Beukman, S. Coward, M. Matthews, M. Fellows, M. Jiang, M. Dennis, and J. Foerster. Refining Minimax Regret for Unsupervised Environment Design. arXiv preprint arXiv:2402.12284, 2024a.
- M. Beukman, S. Coward, M. Matthews, M. Fellows, M. Jiang, M. Dennis, and J. Foerster. Refining Minimax Regret for Unsupervised Environment Design. arXiv preprint arXiv:2402.12284, 2024b.
- J. Bruce, M. D. Dennis, A. Edwards, J. Parker-Holder, Y. Shi, E. Hughes, M. Lai, A. Mavalankar, R. Steigerwald, C. Apps, et al. Genie: Generative interactive environments. In *Forty-first International Conference on Machine Learning*, 2024.
- S. Chaiklin et al. The zone of proximal development in Vygotsky's analysis of learning and instruction. *Vygotsky's educational theory in cultural context*, 1(2):39–64, 2003.
- C.-A. Cheng, A. Nie, and A. Swaminathan. Trace is the Next AutoDiff: Generative Optimization with Rich Feedback, Execution Traces, and LLMs. *arXiv preprint arXiv:2406.16218*, 2024.
- E. Choi, A. Ahmadian, M. Geist, O. Pietquin, and M. G. Azar. Self-Improving Robust Preference Optimization. *arXiv preprint arXiv:2406.01660*, 2024.
- P. F. Christiano, J. Leike, T. Brown, M. Martic, S. Legg, and D. Amodei. Deep reinforcement learning from human preferences. Advances in neural information processing systems, 30, 2017.
- G. Cui, L. Yuan, N. Ding, G. Yao, W. Zhu, Y. Ni, G. Xie, Z. Liu, and M. Sun. Ultrafeedback: Boosting language models with high-quality feedback. *arXiv preprint arXiv:2310.01377*, 2023.
- N. Das, S. Chakraborty, A. Pacchiano, and S. R. Chowdhury. Provably sample efficient rlhf via active preference optimization. *arXiv preprint arXiv:2402.10500*, 2024.
- P. Dayan and G. E. Hinton. Using expectation-maximization for reinforcement learning. *Neural Computation*, 9 (2):271–278, 1997.
- M. Dennis, N. Jaques, E. Vinitsky, A. Bayen, S. Russell, A. Critch, and S. Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. *Advances in neural information processing systems*, 33:13049–13061, 2020.
- S. Dohare, J. F. Hernandez-Garcia, P. Rahman, A. R. Mahmood, and R. S. Sutton. Maintaining plasticity in deep continual learning. *arXiv preprint arXiv:2306.13812*, 2023.
- H. Dong, W. Xiong, D. Goyal, Y. Zhang, W. Chow, R. Pan, S. Diao, J. Zhang, K. Shum, and T. Zhang. Raft: Reward ranked finetuning for generative foundation model alignment. *arXiv preprint arXiv:2304.06767*, 2023.

- H. Dong, W. Xiong, B. Pang, H. Wang, H. Zhao, Y. Zhou, N. Jiang, D. Sahoo, C. Xiong, and T. Zhang. RLHF Workflow: From Reward Modeling to Online RLHF, 2024.
- A. Dubey, A. Jauhri, A. Pandey, A. Kadian, A. Al-Dahle, A. Letman, A. Mathur, A. Schelten, A. Yang, A. Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.
- Y. Dubois, B. Galambosi, P. Liang, and T. B. Hashimoto. Length-controlled alpacaeval: A simple way to debias automatic evaluators. *arXiv preprint arXiv:2404.04475*, 2024.
- K. Fan. Minimax theorems. Proceedings of the National Academy of Sciences, 39(1):42–47, 1953.
- M. Gerstgrasser, R. Schaeffer, A. Dey, R. Rafailov, H. Sleight, J. Hughes, T. Korbak, R. Agrawal, D. Pai, A. Gromov, et al. Is model collapse inevitable? breaking the curse of recursion by accumulating real and synthetic data. *arXiv preprint arXiv:2404.01413*, 2024.
- I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. Advances in neural information processing systems, 27, 2014.
- C. Gulcehre, T. L. Paine, S. Srinivasan, K. Konyushkova, L. Weerts, A. Sharma, A. Siddhant, A. Ahern, M. Wang, C. Gu, et al. Reinforced self-training (rest) for language modeling. *arXiv preprint arXiv:2308.08998*, 2023.
- Q. Guo, R. Wang, J. Guo, B. Li, K. Song, X. Tan, G. Liu, J. Bian, and Y. Yang. Connecting large language models with evolutionary algorithms yields powerful prompt optimizers. *arXiv preprint arXiv:2309.08532*, 2023.
- S. Guo, B. Zhang, T. Liu, T. Liu, M. Khalman, F. Llinares, A. Rame, T. Mesnard, Y. Zhao, B. Piot, et al. Direct language model alignment from online ai feedback. *arXiv preprint arXiv:2402.04792*, 2024.
- J. Hejna, R. Rafailov, H. Sikchi, C. Finn, S. Niekum, W. B. Knox, and D. Sadigh. Contrastive prefence learning: Learning from human feedback without rl. *arXiv preprint arXiv:2310.13639*, 2023.
- J. Hong, N. Lee, and J. Thorne. Orpo: Monolithic preference optimization without reference model. *arXiv preprint arXiv:2403.07691*, 2(4):5, 2024.
- J. Huang, S. S. Gu, L. Hou, Y. Wu, X. Wang, H. Yu, and J. Han. Large language models can self-improve. arXiv preprint arXiv:2210.11610, 2022.
- E. Hughes, M. Dennis, J. Parker-Holder, F. Behbahani, A. Mavalankar, Y. Shi, T. Schaul, and T. Rocktaschel. Open-Endedness is Essential for Artificial Superhuman Intelligence. *arXiv preprint arXiv:2406.04268*, 2024a.
- E. Hughes, M. Dennis, J. Parker-Holder, F. Behbahani, A. Mavalankar, Y. Shi, T. Schaul, and T. Rocktaschel. Open-Endedness is Essential for Artificial Superhuman Intelligence. *arXiv preprint arXiv:2406.04268*, 2024b.
- A. H. Jiang, D. L.-K. Wong, G. Zhou, D. G. Andersen, J. Dean, G. R. Ganger, G. Joshi, M. Kaminksy, M. Kozuch, Z. C. Lipton, et al. Accelerating deep learning by focusing on the biggest losers. *arXiv preprint arXiv:1910.00762*, 2019.
- D. Jiang, X. Ren, and B. Y. Lin. Llm-blender: Ensembling large language models with pairwise ranking and generative fusion. *arXiv preprint arXiv:2306.02561*, 2023.
- M. Jiang. Learning Curricula in Open-Ended Worlds. arXiv preprint arXiv:2312.03126, 2023.
- M. Jiang, M. Dennis, J. Parker-Holder, J. Foerster, E. Grefenstette, and T. Rocktäschel. Replay-guided adversarial environment design. *Advances in Neural Information Processing Systems*, 34:1884–1897, 2021a.
- M. Jiang, E. Grefenstette, and T. Rocktäschel. Prioritized level replay. In International Conference on Machine *Learning*, pages 4940–4950. PMLR, 2021b.
- K. Kawaguchi and H. Lu. Ordered sgd: A new stochastic optimization framework for empirical risk minimization. In *International Conference on Artificial Intelligence and Statistics*, pages 669–679. PMLR, 2020.
- J. M. Keynes. A treatise on probability. Courier Corporation, 1921.
- R. Khirodkar and K. M. Kitani. Adversarial domain randomization. arXiv preprint arXiv:1812.00491, 2018.

- H. Li, Q. Dong, Z. Tang, C. Wang, X. Zhang, H. Huang, S. Huang, X. Huang, Z. Huang, D. Zhang, et al. Synthetic data (almost) from scratch: Generalized instruction tuning for language models. *arXiv preprint arXiv:2402.13064*, 2024a.
- T. Li, W.-L. Chiang, E. Frick, L. Dunlap, T. Wu, B. Zhu, J. E. Gonzalez, and I. Stoica. From Crowdsourced Data to High-Quality Benchmarks: Arena-Hard and BenchBuilder Pipeline. *arXiv preprint arXiv:2406.11939*, 2024b.
- C. Y. Liu and L. Zeng. Skywork Reward Model Series. https://huggingface.co/Skywork, September 2024. URL https://huggingface.co/Skywork.
- T. Liu, Y. Zhao, R. Joshi, M. Khalman, M. Saleh, P. J. Liu, and J. Liu. Statistical rejection sampling improves preference optimization. *arXiv preprint arXiv:2309.06657*, 2023a.
- W. Liu, W. Zeng, K. He, Y. Jiang, and J. He. What makes good data for alignment? a comprehensive study of automatic data selection in instruction tuning. *arXiv preprint arXiv:2312.15685*, 2023b.
- L. Long, R. Wang, R. Xiao, J. Zhao, X. Ding, G. Chen, and H. Wang. On llms-driven synthetic data generation, curation, and evaluation: A survey. *arXiv preprint arXiv:2406.15126*, 2024.
- H. Luo, Q. Sun, C. Xu, P. Zhao, J. Lou, C. Tao, X. Geng, Q. Lin, S. Chen, and D. Zhang. Wizardmath: Empowering mathematical reasoning for large language models via reinforced evol-instruct. *arXiv preprint arXiv:2308.09583*, 2023.
- Y. Meng, M. Xia, and D. Chen. SimPO: Simple Preference Optimization with a Reference-Free Reward. *arXiv preprint arXiv:2405.14734*, 2024.
- S. Mindermann, J. M. Brauner, M. T. Razzak, M. Sharma, A. Kirsch, W. Xu, B. Höltgen, A. N. Gomez, A. Morisot, S. Farquhar, et al. Prioritized training on points that are learnable, worth learning, and not yet learnt. In *International Conference on Machine Learning*, pages 15630–15649. PMLR, 2022.
- W. Muldrew, P. Hayes, M. Zhang, and D. Barber. Active Preference Learning for Large Language Models. arXiv preprint arXiv:2402.08114, 2024.
- R. Munos, M. Valko, D. Calandriello, M. G. Azar, M. Rowland, Z. D. Guo, Y. Tang, M. Geist, T. Mesnard, A. Michi, et al. Nash learning from human feedback. *arXiv preprint arXiv:2312.00886*, 2023.
- J. F. Nash et al. Non-cooperative games. Princeton University, 1950.
- A. Nie, C.-A. Cheng, A. Kolobov, and A. Swaminathan. The Importance of Directional Feedback for LLM-based Optimizers. *arXiv preprint arXiv:2405.16434*, 2024.
- E. Nikishin, M. Schwarzer, P. D'Oro, P.-L. Bacon, and A. Courville. The primacy bias in deep reinforcement learning. In *International conference on machine learning*, pages 16828–16847. PMLR, 2022.
- L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- R. Y. Pang, W. Yuan, K. Cho, H. He, S. Sukhbaatar, and J. Weston. Iterative reasoning preference optimization. *arXiv preprint arXiv:2404.19733*, 2024.
- J. Parker-Holder, M. Jiang, M. Dennis, M. Samvelyan, J. Foerster, E. Grefenstette, and T. Rocktäschel. Evolving curricula with regret-based environment design. In *International Conference on Machine Learning*, pages 17473–17498. PMLR, 2022.
- A. C. Pigou. Some aspects of welfare economics. The American Economic Review, 41(3):287–302, 1920.
- G. Poesia, D. Broman, N. Haber, and N. D. Goodman. Learning Formal Mathematics From Intrinsic Motivation. *arXiv preprint arXiv:2407.00695*, 2024.
- R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, and C. Finn. Direct preference optimization: Your language model is secretly a reward model. *arXiv preprint arXiv:2305.18290*, 2023.

- C. Rosset, C.-A. Cheng, A. Mitra, M. Santacroce, A. Awadallah, and T. Xie. Direct Nash Optimization: Teaching Language Models to Self-Improve with General Preferences. *arXiv preprint arXiv:2404.03715*, 2024.
- D. J. Russo, B. Van Roy, A. Kazerouni, I. Osband, Z. Wen, et al. A tutorial on thompson sampling. *Foundations* and *Trends*® *in Machine Learning*, 11(1):1–96, 2018.
- A. L. Samuel. Some studies in machine learning using the game of checkers. *IBM Journal of research and development*, 3(3):210–229, 1959.
- M. Samvelyan, A. Khan, M. Dennis, M. Jiang, J. Parker-Holder, J. Foerster, R. Raileanu, and T. Rocktäschel. MAESTRO: Open-ended environment design for multi-agent reinforcement learning. *arXiv preprint arXiv:2303.03376*, 2023.
- L. J. Savage. The theory of statistical decision. *Journal of the American Statistical association*, 46(253):55–67, 1951.
- J. Schmidhuber. A possibility for implementing curiosity and boredom in model-building neural controllers. *In Proc.* of the international conference on simulation of adaptive behavior: From animals to animats, 1991.
- J. Schulman, P. Moritz, S. Levine, M. Jordan, and P. Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.
- J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. arXiv preprint arXiv:1707.06347, 2017.
- H.-P. Schwefel. Evolutionsstrategien für die numerische Optimierung. Springer, 1977.
- A. Setlur, S. Garg, X. Geng, N. Garg, V. Smith, and A. Kumar. RL on Incorrect Synthetic Data Scales the Efficiency of LLM Math Reasoning by Eight-Fold. *arXiv preprint arXiv:2406.14532*, 2024.
- D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou,
 V. Panneershelvam, M. Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.
- D. Silver, S. Singh, D. Precup, and R. S. Sutton. Reward is enough. Artificial Intelligence, 299:103535, 2021.
- A. Singh, J. D. Co-Reyes, R. Agarwal, A. Anand, P. Patil, P. J. Liu, J. Harrison, J. Lee, K. Xu, A. Parisi, et al. Beyond human data: Scaling self-training for problem-solving with language models. *arXiv preprint arXiv:2312.06585*, 2023.
- S. Sukhbaatar, Z. Lin, I. Kostrikov, G. Synnaeve, A. Szlam, and R. Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. *arXiv preprint arXiv:1703.05407*, 2017.
- Z. Sun, Y. Shen, Q. Zhou, H. Zhang, Z. Chen, D. Cox, Y. Yang, and C. Gan. Principle-driven self-alignment of language models from scratch with minimal human supervision. *Advances in Neural Information Processing Systems*, 36, 2024.
- R. S. Sutton, J. Modayil, M. Delp, T. Degris, P. M. Pilarski, A. White, and D. Precup. Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 761–768, 2011.
- F. Tajwar, A. Singh, A. Sharma, R. Rafailov, J. Schneider, T. Xie, S. Ermon, C. Finn, and A. Kumar. Preference fine-tuning of llms should leverage suboptimal, on-policy data. *arXiv preprint arXiv:2404.14367*, 2024.
- Y. Tang, Z. D. Guo, Z. Zheng, D. Calandriello, R. Munos, M. Rowland, P. H. Richemond, M. Valko, B. Á. Pires, and B. Piot. Generalized preference optimization: A unified approach to offline alignment. *arXiv preprint arXiv:2402.05749*, 2024.
- G. Team, R. Anil, S. Borgeaud, Y. Wu, J.-B. Alayrac, J. Yu, R. Soricut, J. Schalkwyk, A. M. Dai, A. Hauth, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

- G. Team, M. Riviere, S. Pathak, P. G. Sessa, C. Hardin, S. Bhupatiraju, L. Hussenot, T. Mesnard, B. Shahriari, A. Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.
- O. E. L. Team, A. Stooke, A. Mahajan, C. Barros, C. Deck, J. Bauer, J. Sygnowski, M. Trebacz, M. Jaderberg, M. Mathieu, et al. Open-ended learning leads to generally capable agents. arXiv preprint arXiv:2107.12808, 2021.
- J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In 2017 IEEE/RSJ international conference on intelligent robots and systems (IROS), pages 23–30. IEEE, 2017.
- H. Tran, C. Glaze, and B. Hancock. Iterative DPO Alignment. Technical report, Snorkel AI, 2023.
- P. Villalobos, J. Sevilla, L. Heim, T. Besiroglu, M. Hobbhahn, and A. Ho. Will we run out of data? Limits of LLM scaling based on human-generated data. *arXiv preprint arXiv:2211.04325*, 2024.
- H. Wang, W. Xiong, T. Xie, H. Zhao, and T. Zhang. Interpretable Preferences via Multi-Objective Reward Modeling and Mixture-of-Experts. *arXiv preprint arXiv:2406.12845*, 2024.
- R. Wang, J. Lehman, J. Clune, and K. O. Stanley. Paired open-ended trailblazer (poet): Endlessly generating increasingly complex and diverse learning environments and their solutions. *arXiv preprint arXiv:1901.01753*, 2019.
- Y. Wang, Y. Kordi, S. Mishra, A. Liu, N. A. Smith, D. Khashabi, and H. Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. *arXiv preprint arXiv:2212.10560*, 2022.
- H. Wu and X. Liu. Double thompson sampling for dueling bandits. Advances in neural information processing systems, 29, 2016.
- Y. Wu, Z. Sun, H. Yuan, K. Ji, Y. Yang, and Q. Gu. Self-play preference optimization for language model alignment. *arXiv preprint arXiv:2405.00675*, 2024.
- W. Xiong, H. Dong, C. Ye, Z. Wang, H. Zhong, H. Ji, N. Jiang, and T. Zhang. Iterative preference learning from human feedback: Bridging theory and practice for rlhf under kl-constraint. In *Forty-first International Conference on Machine Learning*, 2024.
- C. Xu, Q. Sun, K. Zheng, X. Geng, P. Zhao, J. Feng, C. Tao, and D. Jiang. Wizardlm: Empowering large language models to follow complex instructions. *arXiv preprint arXiv:2304.12244*, 2023a.
- J. Xu, A. Lee, S. Sukhbaatar, and J. Weston. Some things are more cringe than others: Preference optimization with the pairwise cringe loss. *arXiv preprint arXiv:2312.16682*, 2023b.
- Z. Xu, F. Jiang, L. Niu, Y. Deng, R. Poovendran, Y. Choi, and B. Y. Lin. Magpie: Alignment Data Synthesis from Scratch by Prompting Aligned LLMs with Nothing. *arXiv preprint arXiv:2406.08464*, 2024.
- F. Xue, Y. Fu, W. Zhou, Z. Zheng, and Y. You. To repeat or not to repeat: Insights from scaling llm under token-crisis. Advances in Neural Information Processing Systems, 36, 2024.
- W. Yuan, R. Y. Pang, K. Cho, S. Sukhbaatar, J. Xu, and J. Weston. Self-rewarding language models. arXiv preprint arXiv:2401.10020, 2024.
- Z. Yuan, H. Yuan, C. Li, G. Dong, K. Lu, C. Tan, C. Zhou, and J. Zhou. Scaling relationship on learning mathematical reasoning with large language models. *arXiv preprint arXiv:2308.01825*, 2023.
- M. Yuksekgonul, F. Bianchi, J. Boen, S. Liu, Z. Huang, C. Guestrin, and J. Zou. TextGrad: Automatic" Differentiation" via Text. arXiv preprint arXiv:2406.07496, 2024.
- E. Zelikman, Y. Wu, J. Mu, and N. Goodman. Star: Bootstrapping reasoning with reasoning. Advances in Neural Information Processing Systems, 35:15476–15488, 2022.
- Y. Zhao, R. Joshi, T. Liu, M. Khalman, M. Saleh, and P. J. Liu. Slic-hf: Sequence likelihood calibration with human feedback. *arXiv preprint arXiv:2305.10425*, 2023.

- L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. Xing, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36: 46595–46623, 2023.
- R. Zheng, H. Guo, Z. Liu, X. Zhang, Y. Yao, X. Xu, Z. Wang, Z. Xi, T. Gui, Q. Zhang, et al. Toward Optimal LLM Alignments Using Two-Player Games. arXiv preprint arXiv:2406.10977, 2024.
- T. Zhi-Xuan, M. Carroll, M. Franklin, and H. Ashton. Beyond preferences in ai alignment. *Philosophical Studies*, pages 1–51, 2024.